

Package ‘bbotk’

January 19, 2022

Title Black-Box Optimization Toolkit

Version 0.5.0

Description Provides a common framework for optimization of black-box functions for other packages, e.g. 'mlr3tuning' or 'mlr3fselect'. It offers various optimization methods e.g. grid search, random search, generalized simulated annealing and iterated racing.

License LGPL-3

URL <https://bbotk.mlr-org.com>, <https://github.com/mlr-org/bbotk>

BugReports <https://github.com/mlr-org/bbotk/issues>

Depends paradox ($\geq 0.7.0$), R ($\geq 3.1.0$)

Imports checkmate ($\geq 2.0.0$), data.table, lgr, methods, mlr3misc ($\geq 0.10.0$), R6

Suggests adagio, emoa, GenSA, irace, knitr, nloptr, progressr, rmarkdown, testthat ($\geq 3.0.0$)

VignetteBuilder knitr

Config/testthat/edition 3

Config/testthat/parallel false

Encoding UTF-8

Language en-US

NeedsCompilation yes

RoxygenNote 7.1.2

Collate 'Archive.R' 'ArchiveBest.R' 'Codomain.R' 'Objective.R' 'ObjectiveRFun.R' 'ObjectiveRFunDt.R' 'OptimInstance.R' 'OptimInstanceMultiCrit.R' 'OptimInstanceSingleCrit.R' 'mlr_optimizers.R' 'Optimizer.R' 'OptimizerCmaes.R' 'OptimizerDesignPoints.R' 'OptimizerGenSA.R' 'OptimizerGridSearch.R' 'OptimizerIrace.R' 'OptimizerNLOptr.R' 'OptimizerRandomSearch.R' 'Progressor.R' 'mlr_terminators.R' 'Terminator.R' 'TerminatorClockTime.R' 'TerminatorCombo.R' 'TerminatorEvals.R' 'TerminatorNone.R'

'TerminatorPerfReached.R' 'TerminatorRunTime.R'
 'TerminatorStagnation.R' 'TerminatorStagnationBatch.R'
 'assertions.R' 'bb_optimize.R' 'bbotk_reflections.R'
 'bibentries.R' 'helper.R' 'helper_irace.R' 'nds_selection.R'
 'sugar.R' 'zzz.R'

Author Marc Becker [cre, aut] (<<https://orcid.org/0000-0002-8115-0400>>),
 Jakob Richter [aut] (<<https://orcid.org/0000-0003-4481-5554>>),
 Michel Lang [aut] (<<https://orcid.org/0000-0001-9754-0393>>),
 Bernd Bischl [aut] (<<https://orcid.org/0000-0001-6002-6980>>),
 Martin Binder [aut],
 Olaf Mersmann [ctb]

Maintainer Marc Becker <marcbecker@posteo.de>

Repository CRAN

Date/Publication 2022-01-19 22:02:45 UTC

R topics documented:

bbotk-package	3
Archive	4
ArchiveBest	7
bb_optimize	8
branin	10
Codomain	11
is_dominated	13
mlr_optimizers	13
mlr_optimizers_cmaes	14
mlr_optimizers_design_points	15
mlr_optimizers_gensa	17
mlr_optimizers_grid_search	19
mlr_optimizers_irace	21
mlr_optimizers_nloptr	24
mlr_optimizers_random_search	26
mlr_terminators	28
mlr_terminators_clock_time	29
mlr_terminators_combo	30
mlr_terminators_evals	32
mlr_terminators_none	34
mlr_terminators_perf_reached	35
mlr_terminators_run_time	37
mlr_terminators_stagnation	38
mlr_terminators_stagnation_batch	40
Objective	41
ObjectiveRfun	44
ObjectiveRfunDt	46
opt	48
OptimInstance	49

OptimInstanceMultiCrit	52
OptimInstanceSingleCrit	53
Optimizer	55
Progressor	56
Terminator	57
trm	60
Index	61

bbotk-package *bbotk: Black-Box Optimization Toolkit*

Description

Provides a common framework for optimization of black-box functions for other packages, e.g. 'mlr3tuning' or 'mlr3fselect'. It offers various optimization methods e.g. grid search, random search, generalized simulated annealing and iterated racing.

Author(s)

Maintainer: Marc Becker <marcbecker@posteo.de> ([ORCID](#))

Authors:

- Jakob Richter <jakob1richter@gmail.com> ([ORCID](#))
- Michel Lang <michellang@gmail.com> ([ORCID](#))
- Bernd Bischl <bernd_bischl@gmx.net> ([ORCID](#))
- Martin Binder <martin.binder@mail.com>

Other contributors:

- Olaf Mersmann <olafm@statistik.tu-dortmund.de> [contributor]

See Also

Useful links:

- <https://bbotk.mlr-org.com>
- <https://github.com/mlr-org/bbotk>
- Report bugs at <https://github.com/mlr-org/bbotk/issues>

Archive

Logging object for objective function evaluations

Description

Container around a [data.table::data.table](#) which stores all performed function calls of the Objective.

S3 Methods

- `as.data.table(archive)`
[Archive](#) -> [data.table::data.table\(\)](#)
Returns a tabular view of all performed function calls of the Objective. The `x_domain` column is unnested to separate columns.

Public fields

`search_space` ([paradox::ParamSet](#))
Search space of objective.

`codomain` ([Codomain](#))
Codomain of objective function.

`start_time` ([POSIXct](#))
Time stamp of when the optimization started. The time is set by the [Optimizer](#).

`check_values` (`logical(1)`)
Determines if points and results are checked for validity.

`data` ([data.table::data.table](#))
Contains all performed [Objective](#) function calls.

Active bindings

`n_evals` (`integer(1)`)
Number of evaluations stored in the archive.

`n_batch` (`integer(1)`)
Number of batches stored in the archive.

`cols_x` (`character()`)
Column names of search space parameters.

`cols_y` (`character()`)
Column names of codomain target parameters.

Methods

Public methods:

- [Archive\\$new\(\)](#)
- [Archive\\$add_evals\(\)](#)
- [Archive\\$best\(\)](#)

- [Archive\\$nds_selection\(\)](#)
- [Archive\\$format\(\)](#)
- [Archive\\$print\(\)](#)
- [Archive\\$clear\(\)](#)
- [Archive\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
Archive$new(search_space, codomain, check_values = TRUE)
```

Arguments:

`search_space` ([paradox::ParamSet](#))

Specifies the search space for the [Optimizer](#). The [paradox::ParamSet](#) describes either a subset of the domain of the [Objective](#) or it describes a set of parameters together with a trafo function that transforms values from the search space to values of the domain. Depending on the context, this value defaults to the domain of the objective.

`codomain` ([paradox::ParamSet](#))

Specifies codomain of function. Most importantly the tags of each output "Parameter" define whether it should be minimized or maximized. The default is to minimize each component.

`check_values` (`logical(1)`)

Should x-values that are added to the archive be checked for validity? Search space that is logged into archive.

Method `add_evals()`: Adds function evaluations to the archive table.

Usage:

```
Archive$add_evals(xdt, xss_trafoed = NULL, ydt)
```

Arguments:

`xdt` ([data.table::data.table\(\)](#))

Set of untransformed points / points from the *search space*. One point per row, e.g. `data.table(x1 = c(1, 3), x2 = c(2, 4))`. Column names have to match ids of the `search_space`. However, `xdt` can contain additional columns.

`xss_trafoed` (`list()`)

Transformed point(s) in the *domain space*.

`ydt` ([data.table::data.table\(\)](#))

Optimal outcome.

Method `best()`: Returns the best scoring evaluation(s). For single-crit optimization, the solution that minimizes / maximizes the objective function. For multi-crit optimization, the Pareto set / front.

Usage:

```
Archive$best(batch = NULL, n_select = 1)
```

Arguments:

`batch` (`integer()`)

The batch number(s) to limit the best results to. Default is all batches.

`n_select` (integer(1L))
Amount of points to select. Ignored for multi-crit optimization.

Returns: `data.table::data.table()`

Method `nds_selection()`: Calculate best points w.r.t. non dominated sorting with hypervolume contribution.

Usage:

```
Archive$nds_selection(batch = NULL, n_select = 1, ref_point = NULL)
```

Arguments:

`batch` (integer())
The batch number(s) to limit the best points to. Default is all batches.

`n_select` (integer(1L))
Amount of points to select.

`ref_point` (numeric())
Reference point for hypervolume.

Returns: `data.table::data.table()`

Method `format()`: Helper for print outputs.

Usage:

```
Archive$format()
```

Method `print()`: Printer.

Usage:

```
Archive$print()
```

Arguments:

... (ignored).

Method `clear()`: Clear all evaluation results from archive.

Usage:

```
Archive$clear()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Archive$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

ArchiveBest

Minimal logging object for objective function evaluations

Description

The `ArchiveBest` stores no data but records the best scoring evaluation passed to `$add_evals()`. The `Archive` API is fully implemented but many parameters are ignored and some methods do nothing. The archive still works with `TerminatorClockTime`, `TerminatorEvals`, `TerminatorNone` and `TerminatorEvals`.

Super class

`bbotk::Archive` -> `ArchiveBest`

Active bindings

`n_evals` (`integer(1)`)
Number of evaluations stored in the archive.

`n_batch` (`integer(1)`)
Number of batches stored in the archive.

Methods

Public methods:

- `ArchiveBest$new()`
- `ArchiveBest$add_evals()`
- `ArchiveBest$best()`
- `ArchiveBest$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
ArchiveBest$new(search_space, codomain, check_values = FALSE)
```

Arguments:

`search_space` (`paradox::ParamSet`)

Specifies the search space for the `Optimizer`. The `paradox::ParamSet` describes either a subset of the domain of the `Objective` or it describes a set of parameters together with a trafo function that transforms values from the search space to values of the domain. Depending on the context, this value defaults to the domain of the objective.

`codomain` (`paradox::ParamSet`)

Specifies codomain of function. Most importantly the tags of each output "Parameter" define whether it should be minimized or maximized. The default is to minimize each component.

`check_values` (`logical(1)`)
ignored.

Method `add_evals()`: Stores the best result in `ydt`.

Usage:

```
ArchiveBest$add_evals(xdt, xss_trafoed = NULL, ydt)
```

Arguments:

`xdt` (`data.table::data.table()`)

Set of untransformed points / points from the *search space*. One point per row, e.g. `data.table(x1 = c(1, 3), x2 = c(2, 4))`. Column names have to match ids of the `search_space`. However, `xdt` can contain additional columns.

`xss_trafoed` (`list()`)

Transformed point(s) in the *domain space*.

`ydt` (`data.table::data.table()`)

Optimal outcome.

Method `best()`: Returns the best scoring evaluation. For single-crit optimization, the solution that minimizes / maximizes the objective function. For multi-crit optimization, the Pareto set / front.

Usage:

```
ArchiveBest$best(m = NULL)
```

Arguments:

`m` (`integer()`)

ignored.

Returns: `data.table::data.table()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ArchiveBest$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

bb_optimize

Black-Box Optimization

Description

This function optimizes a function or [Objective](#) with a given method.

Usage

```
bb_optimize(
  x,
  method = "random_search",
  max_evals = 1000,
  max_time = NULL,
```



```

    ...
)

## S3 method for class ``function``
bb_optimize(
  x,
  method = "random_search",
  max_evals = 1000,
  max_time = NULL,
  lower = NULL,
  upper = NULL,
  maximize = FALSE,
  ...
)

## S3 method for class 'Objective'
bb_optimize(
  x,
  method = "random_search",
  max_evals = 1000,
  max_time = NULL,
  search_space = NULL,
  ...
)

```

Arguments

x	(function Objective).
method	(character(1) Optimizer) Key to retrieve optimizer from mlr_optimizers dictionary or Optimizer .
max_evals	(integer(1)) Number of allowed evaluations.
max_time	(integer(1)) Maximum allowed time in seconds.
...	(named list()) Named arguments passed to objective function. Ignored if Objective is optimized.
lower	(numeric()) Lower bounds on the parameters. If named, names are used to create the domain.
upper	(numeric()) Upper bounds on the parameters.
maximize	(logical()) Logical vector used to create the codomain e.g. c(TRUE, FALSE) -> ps(y1 = p_dbl(tags = "maximize"), y2 = pd_dbl(tags = "minimize")). If named, names are used to create the codomain.
search_space	(paradox::ParamSet).

Value

list of

- "par" - Best found parameters
- "value" - Optimal outcome
- "instance" - [OptimInstanceSingleCrit](#) | [OptimInstanceMultiCrit](#)

Note

If both `max_evals` and `max_time` are NULL, [TerminatorNone](#) is used. This is useful if the [Optimizer](#) can terminate itself. If both are given, [TerminatorCombo](#) is created and the optimization stops if the time or evaluation budget is exhausted.

Examples

```
# function and bounds
fun = function(xs) {
  -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + 10
}

bb_optimize(fun, lower = c(-10, -5), upper = c(10, 5), max_evals = 10)

# function and constant
fun = function(xs, c) {
  -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + c
}

bb_optimize(fun, lower = c(-10, -5), upper = c(10, 5), max_evals = 10, c = 1)

# objective
fun = function(xs) {
  c(z = -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + 10)
}

# define domain and codomain using a `ParamSet` from paradox
domain = ps(x1 = p_dbl(-10, 10), x2 = p_dbl(-5, 5))
codomain = ps(z = p_dbl(tags = "minimize"))
objective = ObjectiveRFun$new(fun, domain, codomain)

bb_optimize(objective, method = "random_search", max_evals = 10)
```

branin

Branin Function

Description

Augmented 2-D Branin function with fidelity parameter.

Usage

```
branin(xs)
```

Arguments

`xs` List with the input for a single point (e.g. `list(x1 = 1, x2 = 2, fidelity = 0.5)`).

Value

```
list(1)
```

Source

Wu J, Toscano-Palmerin S, Frazier PI, Wilson AG (2019). "Practical Multi-fidelity Bayesian Optimization for Hyperparameter Tuning." 1903.04703.

Examples

```
branin(list(x1 = 12, x2 = 2, fidelity = 1))
```

Codomain

Codomain of Function

Description

A set of [Param](#) objects defining the codomain of a function. The parameter set must contain at least one target parameter tagged with "minimize" or "maximize". The codomain may contain extra parameters which are ignored when calling the [Archive](#) methods `$best()`, `$nds_selection()` and `$cols_y`. This class is usually constructed internally from a [paradox::ParamSet](#) when [Objective](#) is initialized.

Super class

```
paradox::ParamSet -> Codomain
```

Active bindings

```
is_target (named logical())
```

Position is TRUE for target [Params](#).

```
target_length (integer())
```

Returns number of target [Params](#).

```
target_ids (character())
```

Number of contained target [Params](#).

```
target_tags (named list() of character())
```

Tags of target [Params](#).

```
maximization_to_minimization (integer())
```

Returns a numeric vector with values -1 and 1. Multiply with the outcome of a maximization problem to turn it into a minimization problem.

Methods

Public methods:

- `Codomain$new()`
- `Codomain$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
Codomain$new(params = named_list())
```

Arguments:

```
params (list())
```

List of [Param](#), named with their respective ID. Parameters are cloned.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Codomain$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

Examples

```
# define objective function
fun = function(xs) {
  c(y = -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + 10)
}

# set domain
domain = ps(
  x1 = p_dbl(-10, 10),
  x2 = p_dbl(-5, 5)
)

# set codomain
codomain = ps(
  y = p_dbl(tags = "maximize"),
  time = p_dbl()
)

# create Objective object
objective = ObjectiveRfun$new(
  fun = fun,
  domain = domain,
  codomain = codomain,
  properties = "deterministic"
)
```

is_dominated	<i>Calculate which points are dominated</i>
--------------	---

Description

Returns which points from a set are dominated by another point in the set.

Usage

```
is_dominated(yamat)
```

Arguments

yamat	(matrix()) A numeric matrix. Each column (!) contains one point.
-------	---

mlr_optimizers	<i>Dictionary of Optimizer</i>
----------------	--------------------------------

Description

A simple [mlr3misc::Dictionary](#) storing objects of class [Optimizer](#). Each optimizer has an associated help page, see `mlr_optimizer_[id]`.

This dictionary can get populated with additional optimizer by add-on packages.

For a more convenient way to retrieve and construct optimizer, see [opt\(\)/opts\(\)](#).

Format

[R6::R6Class](#) object inheriting from [mlr3misc::Dictionary](#).

Methods

See [mlr3misc::Dictionary](#).

See Also

Sugar functions: [opt\(\)](#), [opts\(\)](#)

Examples

```
opt("random_search", batch_size = 10)
```

 mlr_optimizers_cmaes *Optimization via Covariance Matrix Adaptation Evolution Strategy*

Description

OptimizerCmaes class that implements CMA-ES. Calls `adagio::pureCMAES()` from package **adagio**. The algorithm is typically applied to search space dimensions between three and fifty. Lower search space dimensions might crash.

Dictionary

This [Optimizer](#) can be instantiated via the [dictionary mlr_optimizers](#) or with the associated sugar function `opt()`:

```
mlr_optimizers$get("cmaes")
opt("cmaes")
```

Parameters

`sigma` numeric(1)

`start_values` character(1)

Create random start values or based on center of search space? In the latter case, it is the center of the parameters before a trafo is applied.

For the meaning of the control parameters, see `adagio::pureCMAES()`. Note that we have removed all control parameters which refer to the termination of the algorithm and where our terminators allow to obtain the same behavior.

Progress Bars

`$optimize()` supports progress bars via the package **progressr** combined with a [Terminator](#). Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package **progress** as backend; enable with `progressr::handlers("progress")`.

Super class

`bbotk::Optimizer` -> `OptimizerCmaes`

Methods

Public methods:

- `OptimizerCmaes$new()`
- `OptimizerCmaes$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
OptimizerCmaes$new()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OptimizerCmaes$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
if (requireNamespace("adagio")) {
  search_space = domain = ps(
    x1 = p_dbl(-10, 10),
    x2 = p_dbl(-5, 5)
  )

  codomain = ps(y = p_dbl(tags = "maximize"))

  objective_function = function(xs) {
    c(y = -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + 10)
  }

  objective = ObjectiveRfun$new(
    fun = objective_function,
    domain = domain,
    codomain = codomain)

  instance = OptimInstanceSingleCrit$new(
    objective = objective,
    search_space = search_space,
    terminator = trm("evals", n_evals = 10))

  optimizer = opt("cmaes")

  # modifies the instance by reference
  optimizer$optimize(instance)

  # returns best scoring evaluation
  instance$result

  # allows access of data.table of full path of all evaluations
  as.data.table(instance$archive$data)
}
```

Description

OptimizerDesignPoints class that implements optimization w.r.t. fixed design points. We simply search over a set of points fully specified by the user. The points in the design are evaluated in order as given.

In order to support general termination criteria and parallelization, we evaluate points in a batch-fashion of size `batch_size`. Larger batches mean we can parallelize more, smaller batches imply a more fine-grained checking of termination criteria.

Dictionary

This [Optimizer](#) can be instantiated via the [dictionary mlr_optimizers](#) or with the associated sugar function `opt()`:

```
mlr_optimizers$get("design_points")
opt("design_points")
```

Parameters

`batch_size` integer(1)
Maximum number of configurations to try in a batch.

`design` [data.table::data.table](#)
Design points to try in search, one per row.

Progress Bars

`$optimize()` supports progress bars via the package **progressr** combined with a [Terminator](#). Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package **progress** as backend; enable with `progressr::handlers("progress")`.

Super class

```
bbotk::Optimizer -> OptimizerDesignPoints
```

Methods**Public methods:**

- [OptimizerDesignPoints\\$new\(\)](#)
- [OptimizerDesignPoints\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
OptimizerDesignPoints$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OptimizerDesignPoints$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```

library(data.table)
search_space = domain = ps(x = p_dbl(lower = -1, upper = 1))

codomain = ps(y = p_dbl(tags = "minimize"))

objective_function = function(xs) {
  list(y = as.numeric(xs)^2)
}

objective = ObjectiveRfun$new(
  fun = objective_function,
  domain = domain,
  codomain = codomain)

instance = OptimInstanceSingleCrit$new(
  objective = objective,
  search_space = search_space,
  terminator = trm("evals", n_evals = 10))

design = data.table(x = c(0, 1))

optimizer = opt("design_points", design = design)

# Modifies the instance by reference
optimizer$optimize(instance)

# Returns best scoring evaluation
instance$result

# Allows access of data.table of full path of all evaluations
as.data.table(instance$archive)

```

mlr_optimizers_gensa *Optimization via Generalized Simulated Annealing*

Description

OptimizerGenSA class that implements generalized simulated annealing. Calls [GenSA::GenSA\(\)](#) from package **GenSA**.

Dictionary

This [Optimizer](#) can be instantiated via the [dictionary mlr_optimizers](#) or with the associated sugar function `opt()`:

```

mlr_optimizers$get("gensa")
opt("gensa")

```

Parameters

smooth logical(1)
 temperature numeric(1)
 acceptance.param numeric(1)
 verbose logical(1)
 trace.mat logical(1)

For the meaning of the control parameters, see `GenSA::GenSA()`. Note that we have removed all control parameters which refer to the termination of the algorithm and where our terminators allow to obtain the same behavior.

Progress Bars

`$optimize()` supports progress bars via the package **progressr** combined with a **Terminator**. Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package **progressr** as backend; enable with `progressr::handlers("progress")`.

Super class

`bbotk::Optimizer` -> `OptimizerGenSA`

Methods

Public methods:

- `OptimizerGenSA$new()`
- `OptimizerGenSA$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
OptimizerGenSA$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OptimizerGenSA$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Source

Tsallis C, Stariolo DA (1996). “Generalized simulated annealing.” *Physica A: Statistical Mechanics and its Applications*, **233**(1-2), 395–406. doi: [10.1016/s03784371\(96\)002713](https://doi.org/10.1016/s03784371(96)002713).

Xiang Y, Gubian S, Suomela B, Hoeng J (2013). “Generalized Simulated Annealing for Global Optimization: The GenSA Package.” *The R Journal*, **5**(1), 13. doi: [10.32614/rj2013002](https://doi.org/10.32614/rj2013002).

Examples

```

if (requireNamespace("GenSA")) {

  search_space = domain = ps(x = p_dbl(lower = -1, upper = 1))

  codomain = ps(y = p_dbl(tags = "minimize"))

  objective_function = function(xs) {
    list(y = as.numeric(xs)^2)
  }

  objective = ObjectiveRFun$new(
    fun = objective_function,
    domain = domain,
    codomain = codomain)

  instance = OptimInstanceSingleCrit$new(
    objective = objective,
    search_space = search_space,
    terminator = trm("evals", n_evals = 10))

  optimizer = opt("cmaes")

  # Modifies the instance by reference
  optimizer$optimize(instance)

  # Returns best scoring evaluation
  instance$result

  # Allows access of data.table of full path of all evaluations
  as.data.table(instance$archive$data)
}

```

mlr_optimizers_grid_search

Optimization via Grid Search

Description

OptimizerGridSearch class that implements grid search. The grid is constructed as a Cartesian product over discretized values per parameter, see [paradox::generate_design_grid\(\)](#). The points of the grid are evaluated in a random order.

In order to support general termination criteria and parallelization, we evaluate points in a batch-fashion of size `batch_size`. Larger batches mean we can parallelize more, smaller batches imply a more fine-grained checking of termination criteria.

Dictionary

This [Optimizer](#) can be instantiated via the [dictionary mlr_optimizers](#) or with the associated sugar function `opt()`:

```
mlr_optimizers$get("grid_search")
opt("grid_search")
```

Parameters

`resolution` `integer(1)`
Resolution of the grid, see [paradox::generate_design_grid\(\)](#).

`param_resolutions` `named integer()`
Resolution per parameter, named by parameter ID, see [paradox::generate_design_grid\(\)](#).

`batch_size` `integer(1)`
Maximum number of points to try in a batch.

Progress Bars

`$optimize()` supports progress bars via the package [progressr](#) combined with a [Terminator](#). Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package [progress](#) as backend; enable with `progressr::handlers("progress")`.

Super class

`bbotk::Optimizer` -> `OptimizerGridSearch`

Methods**Public methods:**

- `OptimizerGridSearch$new()`
- `OptimizerGridSearch$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
OptimizerGridSearch$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OptimizerGridSearch$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```

search_space = domain = ps(x = p_dbl(lower = -1, upper = 1))

codomain = ps(y = p_dbl(tags = "minimize"))

objective_function = function(xs) {
  list(y = as.numeric(xs)^2)
}

objective = ObjectiveRfun$new(
  fun = objective_function,
  domain = domain,
  codomain = codomain)

instance = OptimInstanceSingleCrit$new(
  objective = objective,
  search_space = search_space,
  terminator = trm("evals", n_evals = 10))

optimizer = opt("grid_search")

# modifies the instance by reference
optimizer$optimize(instance)

# returns best scoring evaluation
instance$result

# allows access of data.table of full path of all evaluations
as.data.table(instance$archive$data)

```

mlr_optimizers_irace *Optimization via Iterated Racing*

Description

OptimizerIrace class that implements iterated racing. Calls `irace::irace()` from package **irace**.

Parameters

`instances` list()

A list of instances where the configurations executed on.

`targetRunnerParallel` function()

A function that executes the objective function with a specific parameter configuration and instance. A default function is provided, see section "Target Runner and Instances".

For the meaning of all other parameters, see `irace::defaultScenario()`. Note that we have removed all control parameters which refer to the termination of the algorithm. Use `TerminatorEvals` instead. Other terminators do not work with `OptimizerIrace`.

Target Runner and Instances

The irace package uses a `targetRunner` script or R function to evaluate a configuration on a particular instance. Usually it is not necessary to specify a `targetRunner` function when using `OptimizerIrace`. A default function is used that forwards several configurations and instances to the user defined objective function. As usually, the user defined function has a `xs`, `xss` or `xdt` parameter depending on the used [Objective](#) class. For irace, the function needs an additional `instances` parameter.

```
fun = function(xs, instances) {
  # function to evaluate configuration in `xs` on instance `instances`
}
```

Archive

The [Archive](#) holds the following additional columns:

- "race" (integer(1))
Race iteration.
- "step" (integer(1))
Step number of race.
- "instance" (integer(1))
Identifies instances across races and steps.
- "configuration" (integer(1))
Identifies configurations across races and steps.

Result

The optimization result (`instance$result`) is the best performing elite of the final race. The reported performance is the average performance estimated on all used instances.

Dictionary

This [Optimizer](#) can be instantiated via the [dictionary](#) `mlr_optimizers` or with the associated sugar function `opt()`:

```
mlr_optimizers$get("irace")
opt("irace")
```

Progress Bars

`$optimize()` supports progress bars via the package [progressr](#) combined with a [Terminator](#). Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package [progress](#) as backend; enable with `progressr::handlers("progress")`.

Super class

```
bbotk::Optimizer -> OptimizerIrace
```

Methods

Public methods:

- `OptimizerIrace$new()`
- `OptimizerIrace$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
OptimizerIrace$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OptimizerIrace$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Source

Lopez-Ibanez M, Dubois-Lacoste J, Caceres LP, Birattari M, Stuetzle T (2016). “The irace package: Iterated racing for automatic algorithm configuration.” *Operations Research Perspectives*, **3**, 43–58. doi: [10.1016/j.orp.2016.09.002](https://doi.org/10.1016/j.orp.2016.09.002).

Examples

```
library(data.table)

search_space = domain = ps(
  x1 = p_dbl(-5, 10),
  x2 = p_dbl(0, 15)
)

codomain = ps(y = p_dbl(tags = "minimize"))

# branin function with noise
# the noise generates different instances of the branin function
# the noise values are passed via the `instances` parameter
fun = function(xdt, instances) {
  a = 1
  b = 5.1 / (4 * (pi^2))
  c = 5 / pi
  r = 6
  s = 10
  t = 1 / (8 * pi)

  data.table(y = (
    a * ((xdt[["x2"]] -
      b * (xdt[["x1"]]^2L) +
      c * xdt[["x1"]] - r)^2) +
    ((s * (1 - t)) * cos(xdt[["x1"]])) +
    unlist(instances)))
```

```

}

objective = ObjectiveRFunc$new(fun = fun, domain = domain, codomain = codomain)

instance = OptimInstanceSingleCrit$new(
  objective = objective,
  search_space = search_space,
  terminator = trm("evals", n_evals = 1000))

# create instances of branin function
instances = rnorm(10, mean = 0, sd = 0.1)

# load optimizer irace and set branin instances
optimizer = opt("irace", instances = instances)

# modifies the instance by reference
optimizer$optimize(instance)

# best scoring configuration
instance$result

# all evaluations
as.data.table(instance$archive)

```

mlr_optimizers_nloptr *Optimization via Non-linear Optimization*

Description

OptimizerNLOptr class that implements non-linear optimization. Calls `nloptr::nloptr()` from package **nloptr**.

Parameters

```

algorithm character(1)
eval_g_ineq function()
xtol_rel numeric(1)
xtol_abs numeric(1)
ftol_rel numeric(1)
ftol_abs numeric(1)
start_values character(1)

```

Create random start values or based on center of search space? In the latter case, it is the center of the parameters before a trafo is applied.

For the meaning of the control parameters, see `nloptr::nloptr()` and `nloptr::nloptr.print.options()`.

The termination conditions `stopval`, `maxtime` and `maxeval` of `nloptr::nloptr()` are deactivated and replaced by the **Terminator** subclasses. The x and function value tolerance termination conditions (`xtol_rel = 10^-4`, `xtol_abs = rep(0.0, length(x0))`, `ftol_rel = 0.0` and `ftol_abs = 0.0`) are still available and implemented with their package defaults. To deactivate these conditions, set them to -1.

Progress Bars

\$optimize() supports progress bars via the package **progressr** combined with a **Terminator**. Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package **progress** as backend; enable with `progressr::handlers("progress")`.

Super class

`bbotk::Optimizer` -> `OptimizerNloptr`

Methods

Public methods:

- `OptimizerNloptr$new()`
- `OptimizerNloptr$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

`OptimizerNloptr$new()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`OptimizerNloptr$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Source

Johnson, G S (2020). "The NLOpt nonlinear-optimization package." <https://github.com/stevengj/nlopt>.

Examples

```
if (requireNamespace("nloptr")) {
  search_space = domain = ps(x = p_dbl(lower = -1, upper = 1))
  codomain = ps(y = p_dbl(tags = "minimize"))
  objective_function = function(xs) {
    list(y = as.numeric(xs)^2)
  }
  objective = ObjectiveRfun$new(
    fun = objective_function,
    domain = domain,
    codomain = codomain)
}
```

```

# We use the internal termination criterion xtol_rel
terminator = trm("none")
instance = OptimInstanceSingleCrit$new(
  objective = objective,
  search_space = search_space,
  terminator = terminator)

optimizer = opt("nloptr", algorithm = "NLOPT_LN_BOBYQA")

# Modifies the instance by reference
optimizer$optimize(instance)

# Returns best scoring evaluation
instance$result

# Allows access of data.table of full path of all evaluations
as.data.table(instance$archive)
}

```

mlr_optimizers_random_search

Optimization via Random Search

Description

OptimizerRandomSearch class that implements a simple Random Search.

In order to support general termination criteria and parallelization, we evaluate points in a batch-fashion of size `batch_size`. Larger batches mean we can parallelize more, smaller batches imply a more fine-grained checking of termination criteria.

Dictionary

This [Optimizer](#) can be instantiated via the [dictionary mlr_optimizers](#) or with the associated sugar function `opt()`:

```

mlr_optimizers$get("random_search")
opt("random_search")

```

Parameters

`batch_size` integer(1)
Maximum number of points to try in a batch.

Progress Bars

`$optimize()` supports progress bars via the package [progressr](#) combined with a [Terminator](#). Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package [progress](#) as backend; enable with `progressr::handlers("progress")`.

Super class

`bbotk::Optimizer` -> `OptimizerRandomSearch`

Methods**Public methods:**

- `OptimizerRandomSearch$new()`
- `OptimizerRandomSearch$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
OptimizerRandomSearch$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OptimizerRandomSearch$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Source

Bergstra J, Bengio Y (2012). “Random Search for Hyper-Parameter Optimization.” *Journal of Machine Learning Research*, **13**(10), 281–305. <https://jmlr.csail.mit.edu/papers/v13/bergstra12a.html>.

Examples

```
search_space = domain = ps(x = p_dbl(lower = -1, upper = 1))

codomain = ps(y = p_dbl(tags = "minimize"))

objective_function = function(xs) {
  list(y = as.numeric(xs)^2)
}

objective = ObjectiveRFun$new(
  fun = objective_function,
  domain = domain,
  codomain = codomain)

instance = OptimInstanceSingleCrit$new(
  objective = objective,
  search_space = search_space,
  terminator = trm("evals", n_evals = 10))

optimizer = opt("random_search")

# modifies the instance by reference
```

```
optimizer$optimize(instance)

# returns best scoring evaluation
instance$result

# allows access of data.table of full path of all evaluations
as.data.table(instance$archive$data)
```

mlr_terminators *Dictionary of Terminators*

Description

A simple [mlr3misc::Dictionary](#) storing objects of class [Terminator](#). Each terminator has an associated help page, see `mlr_terminators_[id]`.

This dictionary can get populated with additional terminators by add-on packages.

For a more convenient way to retrieve and construct terminator, see [trm\(\)/trms\(\)](#).

Format

[R6::R6Class](#) object inheriting from [mlr3misc::Dictionary](#).

Methods

See [mlr3misc::Dictionary](#).

See Also

Sugar functions: [trm\(\)](#), [trms\(\)](#)

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation](#), [mlr_terminators_stagnation](#)

Examples

```
trm("evals", n_evals = 10)
```

mlr_terminators_clock_time

Terminator that stops according to the clock time

Description

Class to terminate the optimization after a fixed time point has been reached (as reported by `Sys.time()`).

Dictionary

This `Terminator` can be instantiated via the dictionary `mlr_terminators` or with the associated sugar function `trm()`:

```
mlr_terminators$get("clock_time")
trm("clock_time")
```

Parameters

`stop_time` `POSIXct(1)`
Terminator stops after this point in time.

Super class

`bbotk::Terminator` -> `TerminatorClockTime`

Methods

Public methods:

- `TerminatorClockTime$new()`
- `TerminatorClockTime$is_terminated()`
- `TerminatorClockTime$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
TerminatorClockTime$new()
```

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorClockTime$is_terminated(archive)
```

Arguments:

`archive` ([Archive](#)).

Returns: `logical(1)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TerminatorClockTime$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation_batch](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```
stop_time = as.POSIXct("2030-01-01 00:00:00")
trm("clock_time", stop_time = stop_time)
```

mlr_terminators_combo *Combine Terminators*

Description

This class takes multiple [Terminator](#)s and terminates as soon as one or all of the included terminators are positive.

Dictionary

This [Terminator](#) can be instantiated via the [dictionary mlr_terminators](#) or with the associated sugar function `trm()`:

```
mlr_terminators$get("combo")
trm("combo")
```

Parameters

any logical(1)
 Terminate iff any included terminator is positive? (not all), default is TRUE.

Super class

`bbotk::Terminator` -> TerminatorCombo

Public fields

terminators (`list()`)
 List of objects of class [Terminator](#).

Methods

Public methods:

- `TerminatorCombo$new()`
- `TerminatorCombo$is_terminated()`
- `TerminatorCombo$print()`
- `TerminatorCombo$remaining_time()`
- `TerminatorCombo$status_long()`
- `TerminatorCombo$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
TerminatorCombo$new(terminators = list(TerminatorNone$new()))
```

Arguments:

`terminators` (`list()`)

List of objects of class [Terminator](#).

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorCombo$is_terminated(archive)
```

Arguments:

`archive` ([Archive](#)).

Returns: `logical(1)`.

Method `print()`: Printer.

Usage:

```
TerminatorCombo$print(...)
```

Arguments:

... (ignored).

Method `remaining_time()`: Returns the remaining runtime in seconds. If `any = TRUE`, the remaining runtime is determined by the time-based terminator with the shortest time remaining. If non-time-based terminators are used and `any = FALSE`, the the remaining runtime is always `Inf`.

Usage:

```
TerminatorCombo$remaining_time(archive)
```

Arguments:

`archive` ([Archive](#)).

Returns: `integer(1)`.

Method `status_long()`: Returns `max_steps` and `current_steps` for each terminator.

Usage:

```
TerminatorCombo$status_long(archive)
```

Arguments:

archive ([Archive](#)).

Returns: `data.table::data.table`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TerminatorCombo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation_batch](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```
trm("combo",
  list(trm("clock_time", stop_time = Sys.time() + 60),
    trm("evals", n_evals = 10)), any = FALSE
)
```

`mlr_terminators_evals` *Terminator that stops after a number of evaluations*

Description

Class to terminate the optimization depending on the number of evaluations. An evaluation is defined by one resampling of a parameter value. The total number of evaluations B is defined as

$$B = n_{\text{evals}} + k * D$$

where D is the dimension of the search space.

Dictionary

This [Terminator](#) can be instantiated via the [dictionary](#) `mlr_terminators` or with the associated sugar function `trm()`:

```
mlr_terminators$get("evals")
trm("evals")
```


Parameters

- n_evals integer(1)
See formula above. Default is 100.
- k integer(1)
See formula above. Default is 0.

Super class

`bbotk::Terminator` -> TerminatorEvals

Methods**Public methods:**

- `TerminatorEvals$new()`
- `TerminatorEvals$is_terminated()`
- `TerminatorEvals$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

`TerminatorEvals$new()`

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

`TerminatorEvals$is_terminated(archive)`

Arguments:

archive ([Archive](#)).

Returns: logical(1).

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`TerminatorEvals$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation_batch](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```

TerminatorEvals$new()

# 5 evaluations in total
trm("evals", n_evals = 5)

# 3 * [dimension of search space] evaluations in total
trm("evals", n_evals = 0, k = 3)

# (3 * [dimension of search space] + 1) evaluations in total
trm("evals", n_evals = 1, k = 3)

```

mlr_terminators_none *Terminator that never stops.*

Description

Mainly useful for optimization algorithms where the stopping is inherently controlled by the algorithm itself (e.g. [OptimizerGridSearch](#)).

Dictionary

This [Terminator](#) can be instantiated via the [dictionary mlr_terminators](#) or with the associated sugar function [trm\(\)](#):

```

mlr_terminators$get("none")
trm("none")

```

Super class

[bbotk::Terminator](#) -> TerminatorNone

Methods**Public methods:**

- [TerminatorNone\\$new\(\)](#)
- [TerminatorNone\\$is_terminated\(\)](#)
- [TerminatorNone\\$clone\(\)](#)

Method [new\(\)](#): Creates a new instance of this [R6](#) class.

Usage:

```
TerminatorNone$new()
```

Method [is_terminated\(\)](#): Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorNone$is_terminated(archive)
```

Arguments:

archive ([Archive](#)).

Returns: logical(1).

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
TerminatorNone$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation_batch](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

mlr_terminators_perf_reached

Terminator that stops when a performance level has been reached

Description

Class to terminate the optimization after a performance level has been hit.

Dictionary

This [Terminator](#) can be instantiated via the [dictionary mlr_terminators](#) or with the associated sugar function [trm\(\)](#):

```
mlr_terminators$get("perf_reached")
trm("perf_reached")
```

Parameters

level numeric(1)

Performance level that needs to be reached, default is 0. Terminates if the performance exceeds (respective measure has to be maximized) or falls below (respective measure has to be minimized) this value.

Super class

[bbotk::Terminator](#) -> TerminatorPerfReached

Methods

Public methods:

- [TerminatorPerfReached\\$new\(\)](#)
- [TerminatorPerfReached\\$is_terminated\(\)](#)
- [TerminatorPerfReached\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
TerminatorPerfReached$new()
```

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorPerfReached$is_terminated(archive)
```

Arguments:

archive ([Archive](#)).

Returns: logical(1).

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TerminatorPerfReached$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation_batch](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```
TerminatorPerfReached$new()  
trm("perf_reached")
```

mlr_terminators_run_time

Terminator that stops according to the run time

Description

Class to terminate the optimization after the optimization process took a number of seconds on the clock.

Dictionary

This [Terminator](#) can be instantiated via the [dictionary mlr_terminators](#) or with the associated sugar function `trm()`:

```
mlr_terminators$get("run_time")
trm("run_time")
```

Parameters

`secs` `numeric(1)`
Maximum allowed time, in seconds, default is 100.

Super class

`bbotk::Terminator` -> `TerminatorRunTime`

Methods

Public methods:

- `TerminatorRunTime$new()`
- `TerminatorRunTime$is_terminated()`
- `TerminatorRunTime$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
TerminatorRunTime$new()
```

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorRunTime$is_terminated(archive)
```

Arguments:

`archive` ([Archive](#)).

Returns: `logical(1)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TerminatorRunTime$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

This terminator only works if `archive$start_time` is set. This is usually done by the [Optimizer](#).

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_stagnation_batch](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```
trm("run_time", secs = 1800)
```

```
mlr_terminators_stagnation
```

Terminator that stops when optimization does not improve

Description

Class to terminate the optimization after the performance stagnates, i.e. does not improve more than threshold over the last `iters` iterations.

Dictionary

This [Terminator](#) can be instantiated via the [dictionary mlr_terminators](#) or with the associated sugar function `trm()`:

```
mlr_terminators$get("stagnation")
trm("stagnation")
```

Parameters

`iters` `integer(1)`
 Number of iterations to evaluate the performance improvement on, default is 10.

`threshold` `numeric(1)`
 If the improvement is less than `threshold`, optimization is stopped, default is 0.

Super class

`bbotk::Terminator` -> `TerminatorStagnation`

Methods

Public methods:

- [TerminatorStagnation\\$new\(\)](#)
- [TerminatorStagnation\\$is_terminated\(\)](#)
- [TerminatorStagnation\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
TerminatorStagnation$new()
```

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorStagnation$is_terminated(archive)
```

Arguments:

archive ([Archive](#)).

Returns: `logical(1)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TerminatorStagnation$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```
TerminatorStagnation$new()  
trm("stagnation", iters = 5, threshold = 1e-5)
```

```
mlr_terminators_stagnation_batch
```

Terminator that stops when optimization does not improve

Description

Class to terminate the optimization after the performance stagnates, i.e. does not improve more than threshold over the last n batches.

Dictionary

This [Terminator](#) can be instantiated via the [dictionary mlr_terminators](#) or with the associated sugar function `trm()`:

```
mlr_terminators$get("stagnation_batch")
trm("stagnation_batch")
```

Parameters

`n` `integer(1)`

Number of batches to evaluate the performance improvement on, default is 1.

`threshold` `numeric(1)`

If the improvement is less than threshold, optimization is stopped, default is 0.

Super class

`bbotk::Terminator` -> `TerminatorStagnationBatch`

Methods

Public methods:

- `TerminatorStagnationBatch$new()`
- `TerminatorStagnationBatch$is_terminated()`
- `TerminatorStagnationBatch$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
TerminatorStagnationBatch$new()
```

Method `is_terminated()`: Is TRUE iff the termination criterion is positive, and FALSE otherwise.

Usage:

```
TerminatorStagnationBatch$is_terminated(archive)
```

Arguments:

`archive` ([Archive](#)).

Returns: logical(1).

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
TerminatorStagnationBatch$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Terminator: [Terminator](#), [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

Examples

```
TerminatorStagnationBatch$new()  
trm("stagnation_batch", n = 1, threshold = 1e-5)
```

Objective

Objective function with domain and co-domain

Description

Describes a black-box objective function that maps an arbitrary domain to a numerical codomain.

Technical details

Objective objects can have the following properties: "noisy", "deterministic", "single-crit" and "multi-crit".

Public fields

id (character(1)).

properties (character()).

domain ([paradox::ParamSet](#))

Specifies domain of function, hence its input parameters, their types and ranges.

codomain ([paradox::ParamSet](#))

Specifies codomain of function, hence its feasible values.

constants ([paradox::ParamSet](#)).

Changeable constants or parameters that are not subject to tuning can be stored and accessed here. Set constant values are passed to \$.eval() and \$.eval_many() as named arguments.

check_values (logical(1))

Active bindings

`xdim` (integer(1))
Dimension of domain.

`ydim` (integer(1))
Dimension of codomain.

Methods**Public methods:**

- [Objective\\$new\(\)](#)
- [Objective\\$format\(\)](#)
- [Objective\\$print\(\)](#)
- [Objective\\$eval\(\)](#)
- [Objective\\$eval_many\(\)](#)
- [Objective\\$eval_dt\(\)](#)
- [Objective\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
Objective$new(
  id = "f",
  properties = character(),
  domain,
  codomain = ps(y = p_dbl(tags = "minimize")),
  constants = ps(),
  check_values = TRUE
)
```

Arguments:

`id` (character(1)).

`properties` (character()).

`domain` ([paradox::ParamSet](#))

Specifies domain of function. The [paradox::ParamSet](#) should describe all possible input parameters of the objective function. This includes their id, their types and the possible range.

`codomain` ([paradox::ParamSet](#))

Specifies codomain of function. Most importantly the tags of each output "Parameter" define whether it should be minimized or maximized. The default is to minimize each component.

`constants` ([paradox::ParamSet](#))

Changeable constants or parameters that are not subject to tuning can be stored and accessed here.

`check_values` (logical(1))

Should points before the evaluation and the results be checked for validity?

Method `format()`: Helper for print outputs.

Usage:

Objective\$format()

Returns: character().

Method print(): Print method.

Usage:

Objective\$print()

Returns: character().

Method eval(): Evaluates a single input value on the objective function. If `check_values = TRUE`, the validity of the point as well as the validity of the result is checked.

Usage:

Objective\$eval(xs)

Arguments:

xs (list())

A list that contains a single x value, e.g. `list(x1 = 1, x2 = 2)`.

Returns: list() that contains the result of the evaluation, e.g. `list(y = 1)`. The list can also contain additional *named* entries that will be stored in the archive if called through the [OptimInstance](#). These extra entries are referred to as *extras*.

Method eval_many(): Evaluates multiple input values on the objective function. If `check_values = TRUE`, the validity of the points as well as the validity of the results are checked. *bbotk* does not take care of parallelization. If the function should make use of parallel computing, it has to be implemented by deriving from this class and overwriting this function.

Usage:

Objective\$eval_many(xss)

Arguments:

xss (list())

A list of lists that contains multiple x values, e.g. `list(list(x1 = 1, x2 = 2), list(x1 = 3, x2 = 4))`.

Returns: `data.table::data.table()` that contains one y-column for single-criteria functions and multiple y-columns for multi-criteria functions, e.g. `data.table(y = 1:2)` or `data.table(y1 = 1:2, y2 = 3:4)`. It may also contain additional columns that will be stored in the archive if called through the [OptimInstance](#). These extra columns are referred to as *extras*.

Method eval_dt(): Evaluates multiple input values on the objective function

Usage:

Objective\$eval_dt(xdt)

Arguments:

xdt (`data.table::data.table()`)

Set of untransformed points / points from the *search space*. One point per row, e.g. `data.table(x1 = c(1, 3), x2 = c(2, 4))`. Column names have to match ids of the `search_space`. However, xdt can contain additional columns.

Returns: `data.table::data.table()` that contains one y-column for single-criteria functions and multiple y-columns for multi-criteria functions, e.g. `data.table(y = 1:2)` or `data.table(y1 = 1:2, y2 = 3:4)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Objective$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

ObjectiveRFun

Objective interface with custom R function

Description

Objective interface where the user can pass a custom R function that expects a list as input. If the return of the function is unnamed, it is named with the ids of the codomain.

Super class

`bbotk::Objective` -> ObjectiveRFun

Active bindings

`fun` (function)
Objective function.

Methods

Public methods:

- `ObjectiveRFun$new()`
- `ObjectiveRFun$eval()`
- `ObjectiveRFun$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
ObjectiveRFun$new(
  fun,
  domain,
  codomain = NULL,
  id = "function",
  properties = character(),
  constants = ps(),
  check_values = TRUE
)
```

Arguments:

`fun` (function)

R function that encodes objective and expects a list with the input for a single point (e.g. `list(x1 = 1, x2 = 2)`) and returns the result either as a numeric vector or a list (e.g. `list(y = 3)`).

`domain` ([paradox::ParamSet](#))

Specifies domain of function. The [paradox::ParamSet](#) should describe all possible input parameters of the objective function. This includes their id, their types and the possible range.

`codomain` ([paradox::ParamSet](#))

Specifies codomain of function. Most importantly the tags of each output "Parameter" define whether it should be minimized or maximized. The default is to minimize each component.

`id` (character(1)).

`properties` (character()).

`constants` ([paradox::ParamSet](#))

Changeable constants or parameters that are not subject to tuning can be stored and accessed here.

`check_values` (logical(1))

Should points before the evaluation and the results be checked for validity?

Method `eval()`: Evaluates input value(s) on the objective function. Calls the R function supplied by the user.

Usage:

```
ObjectiveRFun$eval(xs)
```

Arguments:

`xs` Input values.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ObjectiveRFun$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
# define objective function
fun = function(xs) {
  -(xs[[1]] - 2)^2 - (xs[[2]] + 3)^2 + 10
}

# set domain
domain = ps(
  x1 = p_dbl(-10, 10),
  x2 = p_dbl(-5, 5)
)
```

```

# set codomain
codomain = ps(y = p_dbl(tags = "maximize"))

# create Objective object
obfun = ObjectiveRFuncDt$new(
  fun = fun,
  domain = domain,
  codomain = codomain,
  properties = "deterministic"
)

```

ObjectiveRFuncDt *Objective interface for basic R functions.*

Description

Objective interface where user can pass an R function that works on an `data.table()`.

Super class

`bbotk::Objective` -> ObjectiveRFuncDt

Active bindings

`fun` (function)
Objective function.

Methods

Public methods:

- `ObjectiveRFuncDt$new()`
- `ObjectiveRFuncDt$eval_many()`
- `ObjectiveRFuncDt$eval_dt()`
- `ObjectiveRFuncDt$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```

ObjectiveRFuncDt$new(
  fun,
  domain,
  codomain = NULL,
  id = "function",
  properties = character(),
  constants = ps(),
  check_values = TRUE
)

```

Arguments:

`fun` (function)
 R function that encodes objective and expects an `data.table()` as input whereas each point is represented by one row.

`domain` (`paradox::ParamSet`)
 Specifies domain of function. The `paradox::ParamSet` should describe all possible input parameters of the objective function. This includes their id, their types and the possible range.

`codomain` (`paradox::ParamSet`)
 Specifies codomain of function. Most importantly the tags of each output "Parameter" define whether it should be minimized or maximized. The default is to minimize each component.

`id` (`character(1)`).

`properties` (`character()`).

`constants` (`paradox::ParamSet`)
 Changeable constants or parameters that are not subject to tuning can be stored and accessed here.

`check_values` (`logical(1)`)
 Should points before the evaluation and the results be checked for validity?

Method `eval_many()`: Evaluates multiple input values received as a list, converted to a `data.table()` on the objective function. Missing columns in `xss` are filled with NAs in `xdt`.

Usage:

`ObjectiveRFuncDt$eval_many(xss)`

Arguments:

`xss` (`list()`)

A list of lists that contains multiple x values, e.g. `list(list(x1 = 1, x2 = 2), list(x1 = 3, x2 = 4))`.

Returns: `data.table::data.table()` that contains one y-column for single-criteria functions and multiple y-columns for multi-criteria functions, e.g. `data.table(y = 1:2)` or `data.table(y1 = 1:2, y2 = 3:4)`.

Method `eval_dt()`: Evaluates multiple input values on the objective function supplied by the user.

Usage:

`ObjectiveRFuncDt$eval_dt(xdt)`

Arguments:

`xdt` (`data.table::data.table()`)

Set of untransformed points / points from the *search space*. One point per row, e.g. `data.table(x1 = c(1, 3), x2 = c(2, 4))`. Column names have to match ids of the `search_space`. However, `xdt` can contain additional columns.

Returns: `data.table::data.table()` that contains one y-column for single-criteria functions and multiple y-columns for multi-criteria functions, e.g. `data.table(y = 1:2)` or `data.table(y1 = 1:2, y2 = 3:4)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ObjectiveRFunDt$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

 opt

Syntactic Sugar Optimizer Construction

Description

This function complements [mlr_optimizers](#) with functions in the spirit of `mlr_sugar` from **mlr3**.

Usage

```
opt(.key, ...)
```

```
opts(.keys, ...)
```

Arguments

<code>.key</code>	(character(1)) Key passed to the respective dictionary to retrieve the object.
<code>...</code>	(named list()) Named arguments passed to the constructor, to be set as parameters in the paradox::ParamSet , or to be set as public field. See mlr3misc::dictionary_sugar_get() for more details.
<code>.keys</code>	(character()) Keys passed to the respective dictionary to retrieve multiple objects.

Value

- [Optimizer](#) for `opt()`.
- list of [Optimizer](#) for `opts()`.

Examples

```
opt("random_search", batch_size = 10)
```

 OptimInstance

Optimization Instance with budget and archive

Description

Abstract base class.

Technical details

The [Optimizer](#) writes the final result to the `.result` field by using the `$assign_result()` method. `.result` stores a [data.table::data.table](#) consisting of x values in the *search space*, (transformed) x values in the *domain space* and y values in the *codomain space* of the [Objective](#). The user can access the results with active bindings (see below).

Public fields

[objective](#) ([Objective](#)).
[search_space](#) ([paradox::ParamSet](#)).
[terminator](#) ([Terminator](#)).
[archive](#) ([Archive](#)).
[progressor](#) (`progressor()`)
 Stores progressor function.
[objective_multiplier](#) (`integer()`).

Active bindings

[result](#) ([data.table::data.table](#))
 Get result
[result_x_search_space](#) ([data.table::data.table](#))
 x part of the result in the *search space*.
[result_x_domain](#) (`list()`)
 (transformed) x part of the result in the *domain space* of the objective.
[result_y](#) (`numeric()`)
 Optimal outcome.
[is_terminated](#) (`logical(1)`).

Methods

Public methods:

- [OptimInstance\\$new\(\)](#)
- [OptimInstance\\$format\(\)](#)
- [OptimInstance\\$print\(\)](#)
- [OptimInstance\\$eval_batch\(\)](#)
- [OptimInstance\\$assign_result\(\)](#)

- [OptimInstance\\$objective_function\(\)](#)
- [OptimInstance\\$clear\(\)](#)
- [OptimInstance\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
OptimInstance$new(
  objective,
  search_space = NULL,
  terminator,
  keep_evals = "all",
  check_values = TRUE
)
```

Arguments:

`objective` ([Objective](#)).

`search_space` ([paradox::ParamSet](#))

Specifies the search space for the [Optimizer](#). The [paradox::ParamSet](#) describes either a subset of the domain of the [Objective](#) or it describes a set of parameters together with a trafo function that transforms values from the search space to values of the domain. Depending on the context, this value defaults to the domain of the objective.

`terminator` ([Terminator](#)).

`keep_evals` (`character(1)`)

Keep all or only best evaluations in archive?

`check_values` (`logical(1)`)

Should x-values that are added to the archive be checked for validity? Search space that is logged into archive.

Method `format()`: Helper for print outputs.

Usage:

```
OptimInstance$format()
```

Method `print()`: Printer.

Usage:

```
OptimInstance$print(...)
```

Arguments:

... (ignored).

Method `eval_batch()`: Evaluates all input values in `xdt` by calling the [Objective](#). Applies possible transformations to the input values and writes the results to the [Archive](#).

Before each batch-evaluation, the [Terminator](#) is checked, and if it is positive, an exception of class `terminated_error` is raised. This function should be internally called by the [Optimizer](#).

Usage:

```
OptimInstance$eval_batch(xdt)
```

Arguments:

xdt (data.table::data.table())
 x values as data.table() with one point per row. Contains the value in the *search space* of the **OptimInstance** object. Can contain additional columns for extra information.

Method assign_result(): The **Optimizer** object writes the best found point and estimated performance value here. For internal use.

Usage:

```
OptimInstance$assign_result(xdt, y)
```

Arguments:

xdt (data.table::data.table())
 x values as data.table::data.table() with one row. Contains the value in the *search space* of the **OptimInstance** object. Can contain additional columns for extra information.
 y (numeric(1))
 Optimal outcome.

Method objective_function(): Evaluates (untransformed) points of only numeric values. Returns a numeric scalar for single-crit or a numeric vector for multi-crit. The return value(s) are negated if the measure is maximized. Internally, \$eval_batch() is called with a single row. This function serves as a objective function for optimizers of numeric spaces - which should always be minimized.

Usage:

```
OptimInstance$objective_function(x)
```

Arguments:

x (numeric())
 Untransformed points.

Returns: Objective value as numeric(1), negated for maximization problems.

Method clear(): Reset terminator and clear all evaluation results from archive and results.

Usage:

```
OptimInstance$clear()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OptimInstance$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

 OptimInstanceMultiCrit

Optimization Instance with budget and archive

Description

Wraps a multi-criteria [Objective](#) function with extra services for convenient evaluation. Inherits from [OptimInstance](#).

- Automatic storing of results in an [Archive](#) after evaluation.
- Automatic checking for termination. Evaluations of design points are performed in batches. Before a batch is evaluated, the [Terminator](#) is queried for the remaining budget. If the available budget is exhausted, an exception is raised, and no further evaluations can be performed from this point on.

Super class

`bbotk::OptimInstance -> OptimInstanceMultiCrit`

Active bindings

`result_x_domain (list())`
 (transformed) x part of the result in the *domain space* of the objective.

`result_y (numeric(1))`
 Optimal outcome.

Methods

Public methods:

- `OptimInstanceMultiCrit$new()`
- `OptimInstanceMultiCrit$assign_result()`
- `OptimInstanceMultiCrit$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
OptimInstanceMultiCrit$new(
  objective,
  search_space = NULL,
  terminator,
  keep_evals = "all",
  check_values = TRUE
)
```

Arguments:

`objective` ([Objective](#)).

search_space ([paradox::ParamSet](#))

Specifies the search space for the [Optimizer](#). The [paradox::ParamSet](#) describes either a subset of the domain of the [Objective](#) or it describes a set of parameters together with a trafo function that transforms values from the search space to values of the domain. Depending on the context, this value defaults to the domain of the objective.

terminator ([Terminator](#))

Multi-criteria terminator.

keep_evals ([character\(1\)](#))

Keep all or only best evaluations in archive?

check_values ([logical\(1\)](#))

Should x-values that are added to the archive be checked for validity? Search space that is logged into archive.

Method `assign_result()`: The [Optimizer](#) object writes the best found points and estimated performance values here (probably the Pareto set / front). For internal use.

Usage:

```
OptimInstanceMultiCrit$assign_result(xdt, ydt)
```

Arguments:

xdt ([data.table::data.table\(\)](#))

Set of untransformed points / points from the *search space*. One point per row, e.g. `data.table(x1 = c(1, 3), x2 = c(2, 4))`. Column names have to match ids of the `search_space`. However, xdt can contain additional columns.

ydt ([numeric\(1\)](#))

Optimal outcomes, e.g. the Pareto front.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OptimInstanceMultiCrit$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

OptimInstanceSingleCrit

Optimization Instance with budget and archive

Description

Wraps a single-criteria [Objective](#) function with extra services for convenient evaluation. Inherits from [OptimInstance](#).

- Automatic storing of results in an [Archive](#) after evaluation.
- Automatic checking for termination. Evaluations of design points are performed in batches. Before a batch is evaluated, the [Terminator](#) is queried for the remaining budget. If the available budget is exhausted, an exception is raised, and no further evaluations can be performed from this point on.

Super class

bbotk::OptimInstance -> OptimInstanceSingleCrit

Methods**Public methods:**

- OptimInstanceSingleCrit\$new()
- OptimInstanceSingleCrit\$assign_result()
- OptimInstanceSingleCrit\$clone()

Method new(): Creates a new instance of this R6 class.

Usage:

```
OptimInstanceSingleCrit$new(
  objective,
  search_space = NULL,
  terminator,
  keep_evals = "all",
  check_values = TRUE
)
```

Arguments:

objective (**Objective**).

search_space (**paradox::ParamSet**)

Specifies the search space for the **Optimizer**. The **paradox::ParamSet** describes either a subset of the domain of the **Objective** or it describes a set of parameters together with a trafo function that transforms values from the search space to values of the domain. Depending on the context, this value defaults to the domain of the objective.

terminator (**Terminator**).

keep_evals (character(1))

Keep all or only best evaluations in archive?

check_values (logical(1))

Should x-values that are added to the archive be checked for validity? Search space that is logged into archive.

Method assign_result(): The **Optimizer** object writes the best found point and estimated performance value here. For internal use.

Usage:

```
OptimInstanceSingleCrit$assign_result(xdt, y)
```

Arguments:

xdt (**data.table::data.table()**)

Set of untransformed points / points from the *search space*. One point per row, e.g. `data.table(x1 = c(1, 3), x2 = c(2, 4))`. Column names have to match ids of the *search_space*. However, xdt can contain additional columns.

y (numeric(1))

Optimal outcome.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OptimInstanceSingleCrit$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Optimizer

Optimizer

Description

Abstract Optimizer class that implements the base functionality each Optimizer subclass must provide. A Optimizer object describes the optimization strategy.

A Optimizer object must write its result to the \$assign_result() method of the [OptimInstance](#) at the end in order to store the best point and its estimated performance vector.

Progress Bars

\$optimize() supports progress bars via the package **progressr** combined with a [Terminator](#). Simply wrap the function in `progressr::with_progress()` to enable them. We recommend to use package **progress** as backend; enable with `progressr::handlers("progress")`.

Active bindings

param_set ([paradox::ParamSet](#)).

param_classes (`character()`).

properties (`character()`).

packages (`character()`).

Methods**Public methods:**

- [Optimizer\\$new\(\)](#)
- [Optimizer\\$format\(\)](#)
- [Optimizer\\$print\(\)](#)
- [Optimizer\\$optimize\(\)](#)
- [Optimizer\\$clone\(\)](#)

Method new(): Creates a new instance of this [R6](#) class.

Usage:

```
Optimizer$new(param_set, param_classes, properties, packages = character())
```

Arguments:

param_set ([paradox::ParamSet](#)).

param_classes (`character()`).

properties (`character()`).

packages (character()).

Method format(): Helper for print outputs.

Usage:

Optimizer\$format()

Method print(): Print method.

Usage:

Optimizer\$print()

Returns: (character()).

Method optimize(): Performs the optimization and writes optimization result into [OptimInstance](#). The optimization result is returned but the complete optimization path is stored in [Archive](#) of [OptimInstance](#).

Usage:

Optimizer\$optimize(inst)

Arguments:

inst ([OptimInstance](#)).

Returns: [data.table::data.table](#).

Method clone(): The objects of this class are cloneable with this method.

Usage:

Optimizer\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Progressor

Progressor

Description

Wraps `progressr::progressor()` function and stores current progress.

Public fields

progressor (`progressr::progressor()`).

max_steps (`integer(1)`).

current_steps (`integer(1)`).

unit (`character(1)`).

Methods

Public methods:

- [Progressor\\$new\(\)](#)
- [Progressor\\$update\(\)](#)
- [Progressor\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
Progressor$new(progressor, unit)
```

Arguments:

`progressor` (`progressr::progressor()`)

Progressor function.

`unit` (`character(1)`)

Unit of progress.

Method `update()`: Updates `progressr::progressor()` with current steps.

Usage:

```
Progressor$update(terminator, archive)
```

Arguments:

`terminator` ([Terminator](#)).

`archive` ([Archive](#)).

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Progressor$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Terminator

Abstract Terminator Class

Description

Abstract Terminator class that implements the base functionality each terminator must provide. A terminator is an object that determines when to stop the optimization.

Termination of optimization works as follows:

- Evaluations in a instance are performed in batches.
- Before each batch evaluation, the [Terminator](#) is checked, and if it is positive, we stop.
- The optimization algorithm itself might decide not to produce any more points, or even might decide to do a smaller batch in its last evaluation.

Therefore the following note seems in order: While it is definitely possible to execute a fine-grained control for termination, and for many optimization algorithms we can specify exactly when to stop, it might happen that too few or even too many evaluations are performed, especially if multiple points are evaluated in a single batch (c.f. batch size parameter of many optimization algorithms). So it is advised to check the size of the returned archive, in particular if you are benchmarking multiple optimization algorithms.

Technical details

Terminator subclasses can overwrite `.status()` to support progress bars via the package **progressr**. The method must return the maximum number of steps (`max_steps`) and the currently achieved number of steps (`current_steps`) as a named integer vector.

Public fields

`param_set` [paradox::ParamSet](#)
Set of control parameters for terminator.

`properties` (`character()`)
Set of properties.

`unit` (`character()`)
Unit of steps.

Methods

Public methods:

- [Terminator\\$new\(\)](#)
- [Terminator\\$format\(\)](#)
- [Terminator\\$print\(\)](#)
- [Terminator\\$status\(\)](#)
- [Terminator\\$remaining_time\(\)](#)
- [Terminator\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
Terminator$new(param_set = ps(), properties = character())
```

Arguments:

`param_set` ([paradox::ParamSet](#))
Set of control parameters for terminator.

`properties` (`character()`)
Set of properties.

Method `format()`: Helper for print outputs.

Usage:

```
Terminator$format(with_params = FALSE)
```

Arguments:

`with_params (logical(1))`
Add parameter values to format string.

Method `print()`: Printer.

Usage:

`Terminator$print(...)`

Arguments:

... (ignored).

Method `status()`: Returns how many progression steps are made (`current_steps`) and the amount steps needed for termination (`max_steps`).

Usage:

`Terminator$status(archive)`

Arguments:

`archive` ([Archive](#)).

Returns: named integer(2).

Method `remaining_time()`: Returns remaining runtime in seconds. If the terminator is not time-based, the remaining runtime is Inf.

Usage:

`Terminator$remaining_time(archive)`

Arguments:

`archive` ([Archive](#)).

Returns: integer(1).

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Terminator$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Terminator: [mlr_terminators_clock_time](#), [mlr_terminators_combo](#), [mlr_terminators_evals](#), [mlr_terminators_none](#), [mlr_terminators_perf_reached](#), [mlr_terminators_run_time](#), [mlr_terminators_stagnation](#), [mlr_terminators_stagnation](#), [mlr_terminators](#)

`trm`*Syntactic Sugar Terminator Construction*

Description

This function complements [mlr_terminators](#) with functions in the spirit of `mlr_sugar` from **mlr3**.

Usage

```
trm(.key, ...)
```

```
trms(.keys, ...)
```

Arguments

<code>.key</code>	(character(1)) Key passed to the respective dictionary to retrieve the object.
<code>...</code>	(named list()) Named arguments passed to the constructor, to be set as parameters in the paradox::ParamSet , or to be set as public field. See mlr3misc::dictionary_sugar_get() for more details.
<code>.keys</code>	(character()) Keys passed to the respective dictionary to retrieve multiple objects.

Value

- [Terminator](#) for `trm()`.
- list of [Terminator](#) for `trms()`.

Examples

```
trm("evals", n_evals = 10)
```

Index

- * **Optimizer**
 - mlr_optimizers, 13
- * **Terminator**
 - mlr_terminators, 28
 - mlr_terminators_clock_time, 29
 - mlr_terminators_combo, 30
 - mlr_terminators_evals, 32
 - mlr_terminators_none, 34
 - mlr_terminators_perf_reached, 35
 - mlr_terminators_run_time, 37
 - mlr_terminators_stagnation, 38
 - mlr_terminators_stagnation_batch, 40
 - Terminator, 57
- * **datasets**
 - mlr_optimizers, 13
 - mlr_terminators, 28
- adagio::pureCMAES(), 14
- Archive, 4, 4, 7, 11, 22, 29, 31–33, 35–37, 39, 40, 49, 50, 52, 53, 56, 57, 59
- ArchiveBest, 7, 7
- bb_optimize, 8
- bbotk (bbotk-package), 3
- bbotk-package, 3
- bbotk::Archive, 7
- bbotk::Objective, 44, 46
- bbotk::OptimInstance, 52, 54
- bbotk::Optimizer, 14, 16, 18, 20, 22, 25, 27
- bbotk::Terminator, 29, 30, 33–35, 37, 38, 40
- branin, 10
- Codomain, 4, 11
- data.table::data.table, 4, 16, 32, 49, 56
- data.table::data.table(), 4–6, 8, 43, 47, 53, 54
- dictionary, 14, 16, 17, 20, 22, 26, 29, 30, 32, 34, 35, 37, 38, 40, 48, 60
- GenSA::GenSA(), 17, 18
- irace::defaultScenario(), 21
- irace::irace(), 21
- is_dominated, 13
- mlr3misc::Dictionary, 13, 28
- mlr3misc::dictionary_sugar_get(), 48, 60
- mlr_optimizers, 9, 13, 14, 16, 17, 20, 22, 26, 48
- mlr_optimizers_cmaes, 14
- mlr_optimizers_design_points, 15
- mlr_optimizers_gensa, 17
- mlr_optimizers_grid_search, 19
- mlr_optimizers_irace, 21
- mlr_optimizers_nloptr, 24
- mlr_optimizers_random_search, 26
- mlr_terminators, 28, 29, 30, 32–41, 59, 60
- mlr_terminators_clock_time, 28, 29, 32, 33, 35, 36, 38, 39, 41, 59
- mlr_terminators_combo, 28, 30, 30, 33, 35, 36, 38, 39, 41, 59
- mlr_terminators_evals, 28, 30, 32, 32, 35, 36, 38, 39, 41, 59
- mlr_terminators_none, 28, 30, 32, 33, 34, 36, 38, 39, 41, 59
- mlr_terminators_perf_reached, 28, 30, 32, 33, 35, 35, 38, 39, 41, 59
- mlr_terminators_run_time, 28, 30, 32, 33, 35, 36, 37, 39, 41, 59
- mlr_terminators_stagnation, 28, 30, 32, 33, 35, 36, 38, 38, 41, 59
- mlr_terminators_stagnation_batch, 28, 30, 32, 33, 35, 36, 38, 39, 40, 59
- nloptr::nloptr(), 24
- nloptr::nloptr.print.options(), 24
- Objective, 4, 5, 7–9, 11, 22, 41, 49, 50, 52–54

- ObjectiveRFun, [44](#)
- ObjectiveRFunDt, [46](#)
- opt, [48](#)
- opt(), [13](#), [14](#), [16](#), [17](#), [20](#), [22](#), [26](#)
- OptimInstance, [43](#), [49](#), [51–53](#), [55](#), [56](#)
- OptimInstanceMultiCrit, [10](#), [52](#)
- OptimInstanceSingleCrit, [10](#), [53](#)
- Optimizer, [4](#), [5](#), [7](#), [9](#), [10](#), [13](#), [14](#), [16](#), [17](#), [20](#), [22](#), [26](#), [38](#), [48–51](#), [53](#), [54](#), [55](#)
- OptimizerCmaes (mlr_optimizers_cmaes), [14](#)
- OptimizerDesignPoints (mlr_optimizers_design_points), [15](#)
- OptimizerGenSA (mlr_optimizers_gensa), [17](#)
- OptimizerGridSearch, [34](#)
- OptimizerGridSearch (mlr_optimizers_grid_search), [19](#)
- OptimizerIrace (mlr_optimizers_irace), [21](#)
- OptimizerNloptr (mlr_optimizers_nloptr), [24](#)
- OptimizerRandomSearch (mlr_optimizers_random_search), [26](#)
- opts (opt), [48](#)
- opts(), [13](#)

- paradox::generate_design_grid(), [19](#), [20](#)
- paradox::ParamSet, [4](#), [5](#), [7](#), [9](#), [11](#), [41](#), [42](#), [45](#), [47–50](#), [53–55](#), [58](#), [60](#)
- Param, [11](#), [12](#)
- POSIXct, [4](#)
- Progressor, [56](#)

- R6, [5](#), [7](#), [12](#), [14](#), [16](#), [18](#), [20](#), [23](#), [25](#), [27](#), [29](#), [31](#), [33](#), [34](#), [36](#), [37](#), [39](#), [40](#), [42](#), [44](#), [46](#), [50](#), [52](#), [54](#), [55](#), [57](#), [58](#)
- R6::R6Class, [13](#), [28](#)

- Sys.time(), [29](#)

- Terminator, [14](#), [16](#), [18](#), [20](#), [22](#), [24–26](#), [28–41](#), [49](#), [50](#), [52–55](#), [57](#), [57](#), [60](#)
- TerminatorClockTime, [7](#)
- TerminatorClockTime (mlr_terminators_clock_time), [29](#)
- TerminatorCombo, [10](#)
- TerminatorCombo (mlr_terminators_combo), [30](#)
- TerminatorEvals, [7](#), [21](#)
- TerminatorEvals (mlr_terminators_evals), [32](#)
- TerminatorNone, [7](#), [10](#)
- TerminatorNone (mlr_terminators_none), [34](#)
- TerminatorPerfReached (mlr_terminators_perf_reached), [35](#)
- TerminatorRunTime (mlr_terminators_run_time), [37](#)
- TerminatorStagnation (mlr_terminators_stagnation), [38](#)
- TerminatorStagnationBatch (mlr_terminators_stagnation_batch), [40](#)
- trm, [60](#)
- trm(), [28–30](#), [32](#), [34](#), [35](#), [37](#), [38](#), [40](#)
- trms (trm), [60](#)
- trms(), [28](#)