

Package ‘inplace’

August 24, 2020

Version 0.1.2

Date 2020-08-24

Title In-place Operators for R

Description It provides in-place operators for R that are equivalent to '+=', '-=', '*=', '/=' in C++. Those can be applied on integer|double vectors|matrices. You have also access to sweep operations (in-place).

License GPL-3

Language en-US

Encoding UTF-8

LazyData true

ByteCompile true

RoxygenNote 7.1.1

LinkingTo Rcpp

Imports Rcpp

Suggests spelling, data.table, testthat, covr

URL <https://github.com/privefl/inplace>

BugReports <https://github.com/privefl/inplace/issues>

NeedsCompilation yes

Author Florian Privé [aut, cre]

Maintainer Florian Privé <florian.prive.21@gmail.com>

Repository CRAN

Date/Publication 2020-08-24 13:50:02 UTC

R topics documented:

inplace-op	2
inplace-sweep	2

Index	4
--------------	----------

inplace-op

In-place operators

Description

In-place operators

Usage

`x %*<-% value`

`x %+<-% value`

`x %-<-% value`

`x %/<-% value`

Arguments

`x` Variable.

`value` Value.

Value

NULL (invisibly).

Examples

```
mat <- matrix(1:4, 2)
mat
mat %+<-% 2
mat
```

inplace-sweep

Sweep

Description

Sweep

Usage

`sweep1_in_place(x, STATS, FUN = c("-", "+", "*", "/"))`

`sweep2_in_place(x, STATS, FUN = c("-", "+", "*", "/"))`

Arguments

x	a matrix.
STATS	the summary statistic which is to be swept out.
FUN	the function to be used to carry out the sweep.

Value

NULL, invisibly.

Examples

```
x <- matrix(1:6, 2)
sweep(x, 2, 1:3)
x
sweep2_in_place(x, 1:3)
x
```

Index

`%*%-%` (inplace-op), [2](#)
`%+%-%` (inplace-op), [2](#)
`%-%-%` (inplace-op), [2](#)
`%/<-%` (inplace-op), [2](#)

`inplace-op`, [2](#)
`inplace-sweep`, [2](#)

`sweep1_in_place` (inplace-sweep), [2](#)
`sweep2_in_place` (inplace-sweep), [2](#)