

Best Practice for newline in LaTeX table

Hao

2019-03-15

Since many people have asked me this question (#157, this SO question, etc.), I feel like I should document it out. :)

Wrapping texts and make newlines may seem to be the same but they are actually quite different. Thinking about when you “wrap texts” in your text editor, you have a fixed width window and the texts will be automatically wrapped. It’s like a passive skill (in games :P). However, when you are trying to make newlines, you are inserting the linebreak by yourself and it’s mostly like an active skill you need to cast. For these two tasks, LaTeX provides two totally different approaches.

Text wrapping

If you are only trying stop your texts from “overflowing”, you can get it done by setting a fixed width with `kableExtra::column_spec`. This is the most recommended practice as it’s fairly straightforward. The column width controls the width for both table header and table body.

```
library(kableExtra); library(dplyr)
dt <- tibble(
  Items = c("Item 1", "Item 2", "Item 3"),
  Text_1 = c("Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin vehicula tempor ex. Morbi malesuada sagittis turpis, at venenatis nisl luctus a.
  Text_2 = c("Duis posuere placerat magna, ac aliquam lorem viverra non. Ut ultrices tempus eros, quis sodales libero commodo non. In non neque ut lacus vestibulum dictum a quis ipsum.
)
```

```
kable(dt, "latex", booktabs = T,
      col.names = c("Item", "Short Title", "Very Very Very Very Very Very Long Title")) %>%
  column_spec(2:3, width = "5cm")
```

Item	Short Title	Very Very Very Very Very Very Long Title
Item 1	Lorem ipsum dolor sit amet, consectetur adipiscing elit. Proin vehicula tempor ex. Morbi malesuada sagittis turpis, at venenatis nisl luctus a.	Duis posuere placerat magna, ac aliquam lorem viverra non. Ut ultrices tempus eros, quis sodales libero commodo non. In non neque ut lacus vestibulum dictum a quis ipsum.
Item 2	In eu urna at magna luctus rhoncus quis in nisl. Fusce in velit varius, posuere risus et, cursus augue. Duis eleifend aliquam ante, a aliquet ex tincidunt in.	Aenean ut justo interdum, laoreet enim nec, viverra eros. Donec vel pharetra nunc. Suspendisse vel ipsum ac lectus semper aliquam ac a orci. Suspendisse libero mauris, egestas semper auctor sit amet, tempor et orci.
Item 3	Vivamus venenatis egestas eros ut tempus. Vivamus id est nisi. Aliquam molestie erat et sollicitudin venenatis. In ac lacus at velit scelerisque mattis.	Phasellus quis neque aliquet, finibus nunc eget, lacinia neque. Sed auctor lectus vel ex scelerisque commodo.

Table 1: Main Title
Subtitle

Item (Name)	Value (Number)
Hello World	10
This is a cat	100

Insert linebreak in table

In LaTeX, to make linebreaks in table cells, people usually use the `makecell` package. `kableExtra` 0.8.0 comes with a function called `linebreak` to facilitate that. Basically, this function will scan the existence of `\n`. If `\n` exists, it will put the texts in a `makecell` statement. It works in a very similar way with `cell_spec` so you will need to put `escape = F` in `kable`.

```
linebreak("a\nb")
```

```
## [1] "\\makecell[1]{a\\b}"
```

When you have `\n` in your data frame, you can either change the value manually or simply use it with `dplyr::mutate_all`.

```
dt2 <- data.frame(
  Item = c("Hello\nWorld", "This\nis a cat"),
  Value = c(10, 100)
)

dt2 %>%
  mutate_all(linebreak) %>%
  kable("latex", booktabs = T, escape = F,
        caption = "Main Title\\SubTitle",
        col.names = linebreak(c("Item\n(Name)", "Value\n(Number)"), align = "c"))
```

Note that linebreaks in table captions should be treated in a different way. You will need to insert the linebreak (`\\`) by yourself manually, which is easier than using `linebreak`. `linebreak` doesn't work because it put things in a `makecell`, which doesn't work in caption (as it's not a cell :P). At the same time, if you are using `kableExtra` 0.9.0 or any previous version, you need to load the `caption` package in LaTeX by yourself.

header-includes:

```
- \usepackage{caption}
```

Linebreak in other kableExtra functions

If you have a need to put a linebreak in `kableExtra` functions such as `add_header_above` and `pack_rows`, just go ahead and use `\n` directly (in `kableExtra` \geq 0.8.0) and it will be automatically converted. Note that this feature is also controlled by the `escape` option in those functions.

```
dt2 %>%
  mutate_all(linebreak) %>%
  kable("latex", booktabs = T, escape = F,
        col.names = linebreak(c("Item\n(Name)", "Value\n(Number)"), align = "c")) %>%
  add_header_above(c("Combined\nTitle" = 2)) %>%
  pack_rows("Group\n1", 2, 2)
```

Combined Title	
Item (Name)	Value (Number)
Hello World	10
Group 1	
This is a cat	100
