

# Package ‘di’

April 11, 2018

**Type** Package

**Title** Deficit Index (DI)

**Version** 1.1.4

**Date** 2018-04-11

**Maintainer** Ilya Y. Zhbannikov <ilya.zhbannikov@duke.edu>

**Description** A set of utilities for calculating the Deficit (frailty) Index (DI) in gerontological studies.

The deficit index was first proposed by Arnold Mitnitski and Kenneth Rockwood and represents a proxy measure of aging and also can be served as

a sensitive predictor of survival. For more information, see

(i) "Accumulation of Deficits as a Proxy Measure of Aging"

by Arnold B. Mitnitski et al. (2001),

The Scientific World Journal 1, <DOI:10.1100/tsw.2001.58>;

(ii) "Frailty, fitness and late-life mortality in relation to chronological and biological age"

by Arnold B Mitnitski et al. (2001),

BMC Geriatrics 2002 2(1), <DOI:10.1186/1471-2318-2-1>.

**RoxygenNote** 6.0.1

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**Imports** scales

**Depends** R (>= 3.3)

**Encoding** UTF-8

**License** GPL-3

**NeedsCompilation** no

**Author** Ilya Y. Zhbannikov [aut, cre]

**Repository** CRAN

**Date/Publication** 2018-04-11 05:24:20 UTC

## R topics documented:

di .....	2
<b>Index</b>	<b>3</b>

---

di	<i>This function calculates the Deficit Index (DI) and returns results as list: di a column-vector containing deficit indexes for each individual and columns that were used to calculate the di.</i>
----	---

---

### Description

This function calculates the Deficit Index (DI) and returns results as list: di a column-vector containing deficit indexes for each individual and columns that were used to calculate the di.

### Usage

```
di(dat, cols = NULL, invert = NULL, rescale = TRUE, age = NULL,
   rescale.custom = NULL, rescale.avoid = NULL, bins = 7,
   visible = FALSE)
```

### Arguments

dat	A data frame. Required parameter.
cols	A list of column names. Default: NULL.
invert	A list of columns which have to be inverted. Default: NULL.
rescale	A flag that tell the program to rescale columns if the values a not 0/1. Default: TRUE.
age	A name of column which represents age of a patient. Default: NULL.
rescale.custom	A custom rescaling. See example below. Default: NULL.
rescale.avoid	A set of column names for which rescaling should be avoided. Default: NULL.
bins	A number of bins for plotting the DI against age from a dataset. Default: 7.
visible	A flag to show DI plot (mean DI in a population by age) Default: FALSE

### Value

A list of two: di a column-vector containing deficit indexes for each individual and columns (rescaled if flag rescale was set to TRUE) that were used to calculate the di.

### Examples

```
library(di)
dd <- data.frame(subj=seq(1:100),
                 var1=rbinom(100,1,.5),
                 var2=rbinom(100,1,.5),
                 var3=rbinom(100,1,.5))
ddi <- di(dd, c("var1", "var2", "var3"))

# Cusom rescaling
ddi <- di(dd, c("var1", "var2", "var3"), rescale.custom=c("var1:0.1:0.5"))
ddi
```

# Index

di, [2](#)