

# Package ‘h3jsr’

January 4, 2022

**Type** Package

**Title** Access Uber's H3 Library

**Version** 1.2.3

**Date** 2022-01-04

**Description**

Provides access to Uber's H3 library for geospatial indexing via its JavaScript transpile 'h3-js' <<https://github.com/uber/h3-js>> and 'V8' <<https://github.com/jeroen/v8>>.

**License** Apache License (>= 2)

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 2.10)

**SystemRequirements** V8 engine version 6+ is needed for modern JS and WASM support. On Debian / Ubuntu install either libv8-dev or libnode-dev, on Fedora use v8-devel.

**Imports** geojsonsf, methods, sf, tidyr, utils, V8 (>= 4.0.0)

**Suggests** covr, dplyr, ggplot2, knitr, rmarkdown, testthat

**RoxygenNote** 7.1.2

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Lauren O'Brien [aut, cre] (<<https://orcid.org/0000-0002-7336-2171>>)

**Maintainer** Lauren O'Brien <[obr1soilau@gmail.com](mailto:obr1soilau@gmail.com)>

**Repository** CRAN

**Date/Publication** 2022-01-04 13:40:01 UTC

## R topics documented:

h3jsr-package . . . . .	3
are_neighbours . . . . .	3
cell_area . . . . .	4
compact . . . . .	4

edge_length . . . . .	5
get_base_cell . . . . .	6
get_centerchild . . . . .	6
get_children . . . . .	7
get_faces . . . . .	8
get_gcdist . . . . .	8
get_kring . . . . .	9
get_kring_list . . . . .	10
get_local_h3 . . . . .	11
get_local_ij . . . . .	12
get_parent . . . . .	13
get_pentagons . . . . .	13
get_res . . . . .	14
get_res0 . . . . .	15
get_ring . . . . .	15
get_uddest . . . . .	16
get_uedge . . . . .	17
get_uedges . . . . .	17
get_udends . . . . .	18
get_udorigin . . . . .	19
grid_distance . . . . .	19
grid_path . . . . .	20
h3_info_table . . . . .	21
h3_to_line . . . . .	22
h3_to_point . . . . .	23
h3_to_polygon . . . . .	24
is_pentagon . . . . .	24
is_rc3 . . . . .	25
is_valid . . . . .	26
is_valid_edge . . . . .	26
point_to_h3 . . . . .	27
polyfill . . . . .	28
res_area . . . . .	29
res_cendist . . . . .	29
res_count . . . . .	30
res_length . . . . .	31
set_to_multipolygon . . . . .	31
uedge_to_line . . . . .	32
uncompact . . . . .	33

---

h3jsr-package	<i>h3jsr: Access Uber's H3 library</i>
---------------	--

---

**Description**

This package uses package **V8** to access the **javascript bindings for Uber's H3 library**

**Author(s)**

**Maintainer:** Lauren O'Brien <obrlsoilau@gmail.com> (**ORCID**)

---

are_neighbours	<i>check if H3 cells are neighbours</i>
----------------	---

---

**Description**

This function checks whether two H3 cells share an edge.

**Usage**

```
are_neighbours(origin = NULL, destination = NULL, simple = TRUE)
```

**Arguments**

origin	Character; 15-character cell index generated by H3. A vector of indexes can also be supplied.
destination	Character; 15-character cell index generated by H3. A vector of indexes can also be supplied.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

Logical; TRUE if neighbours.

**Note**

- The number of indexes supplied to origin and destination must be equal.
- This function will always return false if the indexes are of different resolutions.

**Examples**

```
# Are the following cells neighbours?  
are_neighbours(origin = '86be8d12ffffff', destination = '86be8d127ffffff')
```

---

cell_area	<i>H3 cell area (exact)</i>
-----------	-----------------------------

---

**Description**

This function calculates the exact area of an H3 cell.

**Usage**

```
cell_area(h3_address = NULL, units = c("m2", "km2"), simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
units	Length unit to report in, either square meters or square kilometers.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a numeric vector of length(h3\_address).

**Examples**

```
cell_area(h3_address = '8abe8d12acaffff', 'm2')
```

---

compact	<i>Compact H3 cells</i>
---------	-------------------------

---

**Description**

This function compacts a set of cells of the same resolution into a set of cells across multiple resolutions that represents the same area.

**Usage**

```
compact(h3_addresses = NULL, simple = TRUE)
```

**Arguments**

h3_addresses	Character vector or list of 15-character indices generated by H3 at a single resolution, generally the output of <a href="#">polyfill</a> .
simple	Logical; whether to return a vector of outputs or a list object containing both inputs and outputs.

**Value**

A list of H3 cells with multiple resolutions. The minimum resolution of the output list matches the resolution of the input list.

**Examples**

```
## Not run:
# Give me a compacted representation of County Ashe, NC
nc <- sf::st_read(system.file("shape/nc.shp", package="sf"), quiet = TRUE)
nc1 <- nc[1, ]
nc1 <- sf::st_cast(nc1, 'POLYGON')
fillers <- polyfill(geometry = nc1, res = 6)
compacted <- compact(fillers)

## End(Not run)
```

---

edge_length	<i>H3 edge length (exact)</i>
-------------	-------------------------------

---

**Description**

This function calculates the exact length of an H3 edge.

**Usage**

```
edge_length(h3_address = NULL, units = c("m", "km", "rads"), simple = TRUE)
```

**Arguments**

h3_address	Character; 16-character index generated by H3.
units	Length unit to report in, either meters or kilometers.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a numeric vector of length(h3\_address).

**Examples**

```
edge_length(h3_address = '166be8d12ffffff', 'm')
```

---

get_base_cell	<i>get the base cell of an H3 cell index</i>
---------------	--

---

### Description

This function returns the number of the base (Level 1) cell for an H3 cell idnex.

### Usage

```
get_base_cell(h3_address = NULL, simple = TRUE)
```

### Arguments

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

### Value

By default, an integer vector of length(h3\_address), ranging from 0 to 121.

### Examples

```
# What is Brisbane Town Hall's base cell number?
get_base_cell(h3_address = '8abe8d12acaffff')
```

---

get_centerchild	<i>get central child H3 cell index</i>
-----------------	--

---

### Description

This function returns the central child of a particular H3 cell index at the requested resolution.

### Usage

```
get_centerchild(h3_address = NULL, res = NULL, simple = TRUE)
```

### Arguments

h3_address	Character; 15-character index generated by H3.
res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a list of length(h3\_address). Each list element contains a vector of H3 cells.

**Examples**

```
# What is the central child of this resolution 6 index at resolution 8?
get_centerchild(h3_address = '86be8d12ffffff', res = 8)
```

---

get_children	<i>get child H3 cell indices</i>
--------------	----------------------------------

---

**Description**

This function returns the children of a particular H3 cell at the requested resolution.

**Usage**

```
get_children(h3_address = NULL, res = NULL, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a list of length(h3\_address). Each list element contains a vector of H3 cell indexes.

**Note**

The number of cells returned for each request is  $7^{(\text{parent\_res} - \text{child\_res})}$ , so jumping three levels will return 343 indexes per request. This can cause memory issues with larger requests.

**Examples**

```
# What are the children of this resolution 6 cell index at resolution 8?
get_children(h3_address = '86be8d12ffffff', res = 8)
```

---

get_faces	<i>get the icosahedron faces of an H3 cell index</i>
-----------	--

---

### Description

This function returns the indices of all icosahedron faces intersected by a given H3 cell index.

### Usage

```
get_faces(h3_address = NULL, simple = TRUE)
```

### Arguments

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

### Value

By default, an integer vector of length(h3\_address), ranging from 1 to 20. If 'simple = FALSE', a data.frame with a column of H3 cell indexes and a list-column of faces.

### Examples

```
# Which faces does this h3 cell index intersect?
get_faces(h3_address = '8abe8d12acaffff')
```

---

get_gcdist	<i>Great circle distance</i>
------------	------------------------------

---

### Description

Get the great circle distance between WGS84 lat/long points

### Usage

```
get_gcdist(pt1 = NULL, pt2 = NULL, units = c("m", "km"), simple = TRUE)
```

### Arguments

pt1	'sf' object with point geometry, 'sfc_POINT' object, 'sfg' point, data frame or matrix.
pt2	'sf' object with point geometry, 'sfc_POINT' object, 'sfg' point, data frame or matrix.
units	whether to return the great circle distance in meters or kilometers.
simple	whether to return a numeric vector of distances or a 'data.frame' containing start and end coordinates as well as distance.



**Value**

Numeric vector of point to point distances, or data frame of origin and destination coordinates accompanied by their distances.

**Note**

This functionality also exists in R packages `sp`, `geosphere` and `fields`. H3's version appears to return slightly shorter distances than most other implementations, but is included here for completeness.

**Examples**

```
# distance between Brisbane and Melbourne
bne <- c(153.028, -27.468)
mlb <- c(144.963, -37.814)
get_gcdist(bne, mlb, 'km')
```

---

get\_kring

*Get nearby H3 cell indices*

---

**Description**

This function returns all the H3 cell indices within a specified number of steps from the index supplied.

**Usage**

```
get_kring(h3_address = NULL, ring_size = 1, simple = TRUE)
```

**Arguments**

<code>h3_address</code>	Character; 15-character cell index generated by H3.
<code>ring_size</code>	Character; number of steps away from the central cell. Defaults to 1.
<code>simple</code>	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a list of length(`h3_address`). Each list element contains a character vector of H3 cells.

**Note**

While the parent function name 'kring' may imply returning a donut of cells, it actually returns a patch centered on the input. The number of cells returned for each input index conforms to the [centered hexagonal number sequence](#), so at 'ring\_size = 5', 91 addresses are returned. The first address returned is the input address, the rest follow in a spiral anticlockwise order.

**Examples**

```
# What are all the neighbours of this cell within two steps?
get_kring(h3_address = '86be8d12ffffff', ring_size = 2)
```

---

get_kring_list	<i>Get nearby H3 cell indexes separated by distance</i>
----------------	---

---

**Description**

This function returns all the H3 cell indexes within a specified number of steps from the address supplied, grouped by step.

**Usage**

```
get_kring_list(h3_address = NULL, ring_size = 1, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character cell index generated by H3.
ring_size	Character; number of steps away from the central cell. Defaults to 1.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a list of length(h3\_address). Each list element contains a list of 'length(ring\_size + 1)'. Each of those lists contains a character vector of H3 cell indices belonging to that step away from the input cell.

**Note**

In total, the number of indices returned for each input cell conforms to the **centered hexagonal number sequence**, so at 'ring\_size = 5', 91 cells are returned. Cells are returned in separate lists, one for each step.

**Examples**

```
# What are the nested neighbours of this cell within two steps?
get_kring_list(h3_address = '86be8d12ffffff', ring_size = 2)
```

---

get_local_h3	<i>Get H3 cell from local i, j coordinates</i>
--------------	--

---

### Description

This function returns H3 destination cells for local i, j coordinate pairs anchored by an H3 origin cell.

### Usage

```
get_local_h3(origin = NULL, i = NULL, j = NULL, simple = TRUE)
```

### Arguments

origin	Character; 15-character cell index generated by H3. A vector of indexes can also be supplied.
i	a single i coordinate or vector of same, generated by <a href="#">get_local_ij</a>
j	a single j coordinate or vector of same, generated by <a href="#">get_local_ij</a>
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

### Value

If 'simple = TRUE', a character vector of destination H3 cells. If not, a data frame containing columns origin, i, j, destination.

### Note

- The coordinate space used by this function may have deleted regions or warping due to pentagonal distortion.
- Coordinates are only comparable if they come from the same origin cell.
- Failure may occur if the destination is too far away from the origin or if the destination is on the other side of a pentagon.
- This function is experimental, and its output is not guaranteed to be compatible across different versions of H3.

### Examples

```
# Get local coordinates for a nearby cell
local <- get_local_ij(origin = '86be8d12ffffff', destination = '86be8d127ffffff')

# Convert back to destination cell
get_local_h3(origin = '86be8d12ffffff', i = local[, 1], j = local[, 2])
```



```

simple = FALSE)

plot(local_coords['destination'], pch = 19) # note origin is (0,0)

```

---

get_parent	<i>get parent H3 cell index</i>
------------	---------------------------------

---

### Description

This function returns the parent of a particular H3 cell index at the requested resolution.

### Usage

```
get_parent(h3_address = NULL, res = NULL, simple = TRUE)
```

### Arguments

h3_address	Character; 15-character index generated by H3.
res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

### Value

By default, a logical vector of length(h3\_address).

### Examples

```

# What is the parent of this cell at resolution 6?
get_parent(h3_address = '8abe8d12acaffff', res = 6)

```

---

get_pentagons	<i>get the pentagon indices for an H3 resolution</i>
---------------	--

---

### Description

This function returns the indices of all pentagons occurring at a given H3 resolution.

### Usage

```
get_pentagons(res = NULL, simple = TRUE)
```

**Arguments**

res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return outputs as list of outputs (TRUE) or data frame with both inputs and outputs.

**Value**

By default, a list of length(h3\_address). Each list element contains a vector of twelve H3 addresses. If simple = FALSE, a data frame with a column of input resolutions and a list-column of pentagon indexes for each.

**Examples**

```
# Which indexes are pentagons at resolution 7?
get_pentagons(res = 7)
```

---

get_res	<i>get the resolution of an H3 cell index</i>
---------	---

---

**Description**

This function returns an H3 cell index's resolution level.

**Usage**

```
get_res(h3_address = NULL, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, an integer vector of length(h3\_address), ranging from 1 to 15.

**Examples**

```
# What is the resolution of this H3 cell index?
get_res(h3_address = '8abe8d12acaffff')
```

---

get_res0	<i>Get resolution 0 indexes</i>
----------	---------------------------------

---

**Description**

Get all H3 cell indexes at resolution 0.

**Usage**

```
get_res0()
```

**Value**

length 122 character vector of top-level H3 cell indices.

**Note**

As every index at every resolution > 0 is the descendant of a res 0 index, this can be used with [get\\_children](#) to iterate over H3 indexes at any resolution.

**Examples**

```
res0 <- get_res0()
cell_area(res0[1], 'km2')
```

---

get_ring	<i>Get a donut of H3 cell indexes</i>
----------	---------------------------------------

---

**Description**

This function returns all the H3 cell indexes at the specified step from the address supplied.

**Usage**

```
get_ring(h3_address = NULL, ring_size = 1, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character cell index generated by H3.
ring_size	Character; number of steps away from the central cell. Defaults to 1.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a list of length(h3\_address). Each list element contains a character vector of H3 cells belonging to that step away from the input address.

**Note**

In total, the number of cells returned for each input index is 'ring\_size \\* 6'.

**Examples**

```
# What are the neighbours of this cell at step 2?  
get_ring(h3_address = '86be8d12ffffff', ring_size = 2)
```

---

get_uddest	<i>Get destination cell from directed edge</i>
------------	--

---

**Description**

Get an H3 index representing the destination of a directed edge.

**Usage**

```
get_uddest(h3_edge = NULL, simple = TRUE)
```

**Arguments**

h3_edge	Address of directed edge.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, character vector of h3 cell indexes.

**Examples**

```
# Get the destination cell index of this directed edge index  
get_uddest(h3_edge = '166be8d12ffffff')
```



---

get_udedge	<i>Get a directed edge index</i>
------------	----------------------------------

---

**Description**

Returns an H3 index representing a directed edge for a given origin and destination cell pair.

**Usage**

```
get_udedge(origin = NULL, destination = NULL, simple = TRUE)
```

**Arguments**

origin	Character; 15-character cell index generated by H3. A vector of indexes can also be supplied.
destination	Character; 15-character cell index generated by H3. A vector of indexes can also be supplied.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, character vector of directed edge indexes.

**Note**

The number of cell indexes supplied to origin and destination must be equal.

**Examples**

```
# Get me the directed edge representing the transition between these two cells
get_udedge(origin = '86be8d12ffffff', destination = '86be8d127ffffff')
```

---

get_udedges	<i>Get all directed edge indexes for a given H3 cell</i>
-------------	--

---

**Description**

Get all directed edge indexes for a given H3 cell index.

**Usage**

```
get_udedges(h3_address = NULL, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, list of length(h3\_address). Each list contains a character vector of H3 edge indexes.

**Examples**

```
# Get all the edge indexes for this cell
get_udedges(h3_address = '86be8d12ffffff')
```

---

get_udends	<i>Get origin and destination indexes of directed edge</i>
------------	--

---

**Description**

Get H3 cell indexes representing the origin and destination of a directed edge index.

**Usage**

```
get_udends(h3_edge = NULL, simple = TRUE)
```

**Arguments**

h3_edge	Address of directed edge.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, character matrix of h3 cell indexes.

**Examples**

```
# Get the origin and destination of this directed edge
get_udends(h3_edge = '166be8d12ffffff')
```

---

get_udorigin	<i>Get origin cell index from directed edge</i>
--------------	---

---

**Description**

Get an H3 cell index representing the origin of a directed edge.

**Usage**

```
get_udorigin(h3_edge = NULL, simple = TRUE)
```

**Arguments**

h3_edge	Address of directed edge.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, character vector of H3 indexes.

**Examples**

```
# Get the origin of this directed edge
get_udorigin(h3_edge = '166be8d12ffffff')
```

---

grid_distance	<i>Grid distance between H3 cells</i>
---------------	---------------------------------------

---

**Description**

This function gets the grid distance between two H3 cell indices.

**Usage**

```
grid_distance(origin = NULL, destination = NULL, simple = TRUE)
```

**Arguments**

origin	Character vector or list of 15-character indices generated by H3.
destination	Character vector or list of 15-character indices generated by H3.
simple	Logical; whether to return a vector of outputs or a list object containing both inputs and outputs.

**Value**

The distance between two H3 cells, expressed as the minimum number of hexagon 'steps' required to get from the origin to the destination. Thus, a neighbour cell is one step away, and two cells with one hexagon between them are two steps apart.

**Note**

Input H3 indices must be of the same resolution or results cannot be computed. This function may fail to find the distance between two indices if they are very far apart or on opposite sides of a pentagon.

**Examples**

```
## Not run:
nc <- sf::st_read(system.file("shape/nc.shp", package="sf"), quiet = TRUE)
nc_pts <- sf::st_centroid(nc[c(1, 2), ])
nc_6 <- point_to_h3(nc_pts, res = 6)
# how far apart are these two addresses?
grid_distance(nc_6[1], nc_6[2])

## End(Not run)
```

---

grid_path	<i>Path between H3 cells</i>
-----------	------------------------------

---

**Description**

This function returns a path of H3 cells between a start and end cell (inclusive).

**Usage**

```
grid_path(origin = NULL, destination = NULL, simple = TRUE)
```

**Arguments**

origin	Character vector or list of 15-character indices generated by H3.
destination	Character vector or list of 15-character indices generated by H3.
simple	Logical; whether to return a vector of outputs or a list object containing both inputs and outputs.

**Value**

A vector of h3 cells of form `c(origin, c(path), destination)`.

**Note**

- Input H3 cells must be of the same resolution or results cannot be computed. This function may fail to find the distance between two indexes if they are very far apart or on opposite sides of a pentagon.
- The specific output of this function should not be considered stable across library versions. The only guarantees the library provides are that the line length will be ‘h3\_distance(start, end) + 1’ and that every index in the line will be a neighbor of the preceding index.
- Lines are drawn in grid space, and may not correspond exactly to either Cartesian lines or great arcs

**Examples**

```
## Not run:
nc <- sf::st_read(system.file("shape/nc.shp", package="sf"), quiet = TRUE)
nc_pts <- sf::st_centroid(nc[c(1, 2), ])
nc_6 <- point_to_h3(nc_pts, res = 6)
# find a path between these two addresses:
grid_path(nc_6[1], nc_6[2], simple = TRUE)

## End(Not run)
```

---

h3\_info\_table

*H3 index utility information table*


---

**Description**

A dataset containing information about h3 cell indexes at each resolution, calculated using H3’s built-in functions.

**Usage**

```
h3_info_table
```

**Format**

A data frame with 16 rows and 6 variables:

- h3\_resolution** H3 resolution index number
- avg\_area\_sqm** Average area of an H3 cell index at the given resolution, in square meters.
- avg\_area\_sqkm** Average area of an H3 cell index at the given resolution, in square kilometers.
- avg\_edge\_m** Average edge length of an H3 cell index at the given resolution, in meters.
- avg\_edge\_km** Average edge length of an H3 cell index at the given resolution, in kilometers.
- avg\_cendist\_m** Average distance between cell centers at the given resolution, in meters.
- avg\_cendist\_km** Average distance between cellcenters at the given resolution, in kilometers.
- total\_unique\_indexes** Total number of H3 cells at the given resolution.

**Source**

See also <https://h3geo.org/docs/core-library/restable/>

---

h3_to_line	<i>Convert H3 cell indexes to a line</i>
------------	--

---

**Description**

Return line geometry for a sequence of H3 cell indexes in WGS84 coordinates.

**Usage**

```
h3_to_line(input = NULL, simple = TRUE)

## S3 method for class 'data.frame'
h3_to_line(input = NULL, simple = TRUE)

## S3 method for class 'list'
h3_to_line(input = NULL, simple = TRUE)

## S3 method for class 'character'
h3_to_line(input = NULL, simple = TRUE)
```

**Arguments**

input	Character vector of 15-character indexes generated by H3, a list of such, or a data frame where the last column is a list-column of H3 cell indexes (usually the output of <code>h3jsr::grid_path()</code> ).
simple	Logical; whether to return an ‘sfc_LINestring’ object or an ‘sf’ data frame containing both inputs and outputs.

**Value**

An ‘sfc\_LINestring’ object containing a line for each vector of H3 cell indexes supplied. If `simple = FALSE`, an ‘sf’ object including the input data.

**Note**

This function can accept any arbitrary vector of cell indexes (including cells at multiple resolutions) but results may be unexpected. It is assumed that indexes are supplied in a pre-ordered fashion.

**Examples**

```
# What is the cell index over the Brisbane Town Hall at resolution 10?
brisbane_hex_10 <- h3_to_polygon(input = '8abe8d12acaffff')

# Give me a some nearby cells
hex_sample <- get_kring_list('8abe8d12acaffff', 4)[[1]][[4]][seq(1,18,3)]
hex_sample_polys <- h3_to_polygon(hex_sample)

# find connecting paths
paths <- grid_path(rep('8abe8d12acaffff', 6), hex_sample)

# make lines
lines <- h3_to_line(paths)

## Not run:
plot(hex_sample_polys, reset = FALSE)
plot(brisbane_hex_10, add = TRUE)
plot(lines, col = 'red', add = TRUE)

## End(Not run)
```

---

h3\_to\_point

*Convert H3 cell index to point location*


---

**Description**

This function takes a H3 cell index and returns its center coordinates in WGS84.

**Usage**

```
h3_to_point(h3_address = NULL, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, an 'sfc\_POINT' object of 'length(h3\_address)'. EPSG:WGS84.

**Examples**

```
# Where is the center of the hexagon over the Brisbane Town Hall at resolution 10?
brisbane_10 <- h3_to_point(h3_address = '8abe8d12acaffff')
```

---

h3_to_polygon	<i>Get the boundary of an H3 cell index</i>
---------------	---

---

### Description

This function takes an H3 cell index and returns its bounding shape (usually a hexagon) in WGS84.

### Usage

```
h3_to_polygon(input = NULL, simple = TRUE)
```

### Arguments

input	Character; 15-character index generated by H3, or a vector or list of same, or a data frame where the first column contains H3 addresses.
simple	Logical; whether to return an 'sfc_POLYGON' object or an 'sf' data frame containing both inputs and outputs.

### Value

By default, an 'sfc\_POLYGON' object of 'length(input)'. If an appropriately formatted data frame is supplied, an 'sf' data frame containing input attributes and geometry.

### Examples

```
# What is the hexagon over the Brisbane Town Hall at resolution 10?
brisbane_hex_10 <- h3_to_polygon(input = '8abe8d12acaffff')

# Give me some of the cells over Brisbane Town Hall as an sf object
bth <- sf::st_sfc(sf::st_point(c(153.023503, -27.468920)), crs = 4326)
bth_addys <- unlist(point_to_h3(bth, res = seq(10, 15)), use.names = FALSE)
bth_hexes <- h3_to_polygon(input = bth_addys)
plot(bth_hexes, axes = TRUE)
```

---

is_pentagon	<i>check if H3 cell index is a pentagon</i>
-------------	---

---

### Description

This function checks whether a H3 cell index refers to one of the pentagons that occur at icosahedron corners.

### Usage

```
is_pentagon(h3_address = NULL, simple = TRUE)
```



**Arguments**

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a logical vector of length(h3\_address).

**Examples**

```
# is the following cell index a pentagon?
is_pentagon(h3_address = '8abe8d12acaffff')
```

---

is_rc3	<i>check if H3 cell index is in a Class III resolution</i>
--------	--

---

**Description**

This function checks whether a H3 cell index is in a Class III resolution (rotated versus the icosahedron and subject to shape distortion adding extra points on icosahedron edges).

**Usage**

```
is_rc3(h3_address = NULL, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a logical vector of length(h3\_address).

**Examples**

```
# is the following cell index Class III?
is_rc3(h3_address = '8abe8d12acaffff')
```

---

is_valid	<i>check H3 cell index</i>
----------	----------------------------

---

**Description**

This function checks whether an H3 cell index is valid.

**Usage**

```
is_valid(h3_address = NULL, simple = TRUE)
```

**Arguments**

h3_address	Character; 15-character index generated by H3.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a logical vector of length(h3\_address).

**Examples**

```
# is the following cell index valid?
is_valid(h3_address = '8abe8d12acaffff')
```

---

is_valid_edge	<i>Check H3 directed edge index</i>
---------------	-------------------------------------

---

**Description**

This function checks whether an H3 directed edge index is valid.

**Usage**

```
is_valid_edge(h3_edge = NULL, simple = TRUE)
```

**Arguments**

h3_edge	Address of directed edge.
simple	Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, a logical vector of length(h3\_edge).

**Examples**

```
# is the following directed edge index valid?
is_valid_edge(h3_edge = '166be8d12ffffff')
```

---

point_to_h3	<i>Convert point location to H3 cell index</i>
-------------	--

---

**Description**

This function takes point location data and returns a H3 cell index for each point at the chosen resolution(s).

**Usage**

```
point_to_h3(input = NULL, res = NULL, simple = TRUE)
```

**Arguments**

input	'sf' object with point geometry, 'sfc_POINT' object, 'sfg' point, data frame or matrix.
res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return outputs as character vector where possible.

**Value**

- if 'simple = TRUE' and one resolution is requested, a character vector of H3 addresses.
- if 'simple = TRUE' and multiple resolutions are requested, a data frame of H3 addresses.
- if 'simple = FALSE' and a matrix, sfc or sfg object is supplied, a data frame of H3 addresses.
- if 'simple = FALSE' and a data frame or sf object with other attributes is supplied, a data frame of non-spatial attributes with new columns containing addresses for one or more H3 resolutions.

**Note**

While multiple resolutions can be requested for multiple points, be aware of the memory demand on large datasets.

**Examples**

```
# where is the Brisbane Town Hall at resolution 15?
bth <- sf::st_sfc(sf::st_point(c(153.023503, -27.468920)), crs = 4326)
bth_15 <- point_to_h3(bth, res = 15)

# where is it at several resolutions?
bth_many <- point_to_h3(bth, res = seq(10, 15), simple = FALSE)
```

---

polyfill

*Get H3 cell index within a polygon*

---

### Description

This function returns all the H3 cell index within the supplied polygon geometry.

### Usage

```
polyfill(geometry = NULL, res = NULL, simple = TRUE)
```

### Arguments

geometry	'sf' object of type 'POLYGON' or 'MULTIPOLYGON'.
res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return a vector of outputs or an sf object containing both inputs and outputs.

### Value

By default, a list of length(h3\_address). Each list element contains a character vector of H3 cell indices belonging to that geometry. A result of NA indicates that no H3 cell indices of the chosen resolution are centered over the geometry.

### Note

This function will be slow with a large number of polygons, and/or polygons that are large relative to the hexagon area at the chosen resolution. A message is printed to console where the total input area is (roughly) > 100000x the area of the chosen H3 resolution.

### Examples

```
# Which level 5 H3 cell indices have centers inside County Ashe, NC?  
nc <- sf::st_read(system.file("shape/nc.shp", package="sf"), quiet = TRUE)  
nc1 <- nc[1, ]  
fillers <- polyfill(geometry = nc1, res = 5)
```

---

res_area	<i>Get H3 cell area</i>
----------	-------------------------

---

**Description**

This function returns the average area of an H3 cell at a given resolution.

**Usage**

```
res_area(res = NULL, units = c("m2", "km2"), fast = TRUE)
```

**Arguments**

res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
units	Areal unit to report in, either square meters or square kilometers.
fast	Logical; whether to retrieve values from a locally stored table or reclaculate from source.

**Value**

Numeric; average H3 cell area.

**Examples**

```
# Return average H3 cell area at each resolution in square meters
res_area(res = seq(0, 15), units = 'm2')
```

---

res_cendist	<i>Get average distance between H3 cell centers</i>
-------------	---

---

**Description**

This function returns the average distance between the center of H3 cells at a given resolution.

**Usage**

```
res_cendist(res = NULL, units = c("m", "km"), fast = TRUE)
```

**Arguments**

res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
units	Length unit to report in, either meters or kilometers.
fast	Logical; whether to retrieve values from a locally stored table or reclaculate from source.

**Value**

Numeric; H3 cell center separation distance.

**Note**

This isn't in the core library but may be useful.

**Examples**

```
# Return average H3 cell separation distance at each resolution in kilometers
res_cendist(res = seq(0, 15), units = 'km')
```

---

res\_count

*Get total H3 cells*

---

**Description**

This function returns total number of H3 cells at a given resolution.

**Usage**

```
res_count(res = NULL, fast = TRUE)
```

**Arguments**

res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
fast	Logical; whether to retrieve values from a locally stored table or recalculate from source.

**Value**

Numeric; H3 cell count.

**Examples**

```
# Return H3 cell count for resolution 8
res_count(res = 8)
```

---

res_length	<i>Get H3 cell edge length</i>
------------	--------------------------------

---

**Description**

This function returns the average edge length of an H3 cell edge at a given resolution.

**Usage**

```
res_length(res = NULL, units = c("m", "km"), fast = TRUE)
```

**Arguments**

res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
units	Length unit to report in, either meters or kilometers.
fast	Logical; whether to retrieve values from a locally stored table or recalculate from source.

**Value**

Numeric; H3 cell edge length

**Note**

This value is also the hexagon circumradius.

**Examples**

```
# Return average H3 cell edge length at each resolution in kilometers
res_length(res = seq(0, 15), units = 'km')
```

---

set_to_multipolygon	<i>Get geometry for a set of H3 cells</i>
---------------------	---

---

**Description**

This function returns geometry associated with a set of H3 cells, as a single 'sfc\_MULTIPOLYGON'.

**Usage**

```
set_to_multipolygon(h3_addresses = NULL, simple = TRUE)
```

**Arguments**

`h3_addresses` Character vector or list of 15-character cell indices generated by H3.  
`simple` Logical; whether to return an 'sfc\_MULTIPOLYGON' or an 'sf' object including the input cells.

**Value**

By default, object of type 'sfc\_MULTIPOLYGON' of length 1.

**Note**

The geometry returned by this function will not be valid where the addresses supplied overlap at the same resolution. The main use case for this function appears to be visualising the outputs of 'polyfill()' and 'compact()'.

**Examples**

```
## Not run:
# Give me the outline of the cells around Brisbane Town Hall at
# resolution 10 (not run as slow-ish)
bth <- sf::st_sfc(sf::st_point(c(153.023503, -27.468920)), crs = 4326)
bth_10 <- point_to_h3(bth, res = 10)
bth_patch <- get_kring(h3_address = bth_10, ring_size = 2)
bth_patch_sf <- set_to_multipolygon(bth_patch)

## End(Not run)
```

---

udedge\_to\_line

*Get the geometry of an H3 edge*

---

**Description**

This function takes an H3 unidirectional edge address and returns the coordinates of its geometry in WGS84.

**Usage**

```
udedge_to_line(h3_edge = NULL, simple = TRUE)
```

**Arguments**

`h3_edge` Address of directed edge.  
`simple` Logical; whether to return a vector of outputs or a data frame containing both inputs and outputs.

**Value**

By default, an object of type 'sfc\_LINestring'.



**Examples**

```
# get me the shape of this edge
udedge_to_line(h3_edge = '166be8d12ffffffff')
```

---

uncompact

*Uncompact H3 cell indices*


---

**Description**

This function uncompact a compacted set of H3 cells to indices of the target resolution.

**Usage**

```
uncompact(h3_addresses = NULL, res = NULL, simple = TRUE)
```

**Arguments**

h3_addresses	Character vector or list of 15-character cell indices generated by H3.
res	Integer; Desired H3 resolution. See <a href="https://h3geo.org/docs/core-library/restable/">https://h3geo.org/docs/core-library/restable/</a> for allowable values and related dimensions.
simple	Logical; whether to return a vector of outputs or a list object containing both inputs and outputs.

**Value**

A list of H3 cell indices of the chosen resolution.

**Examples**

```
## Not run:
# Give me a compacted representation of County Ashe, NC
nc <- sf::st_read(system.file("shape/nc.shp", package="sf"), quiet = TRUE)
nc1 <- nc[, ]
nc1 <- sf::st_cast(nc1, 'POLYGON')
fillers <- polyfill(geometry = nc1, res = 6)
compact <- compact(fillers)
# uncompact to resolution 7
uncompact <- uncompact(compact, res = 7)

## End(Not run)
```

# Index

## \* datasets

h3\_info\_table, 21

are\_neighbours, 3

cell\_area, 4

compact, 4

edge\_length, 5

get\_base\_cell, 6

get\_centerchild, 6

get\_children, 7, 15

get\_faces, 8

get\_gcdist, 8

get\_kring, 9

get\_kring\_list, 10

get\_local\_h3, 11

get\_local\_ij, 11, 12

get\_parent, 13

get\_pentagons, 13

get\_res, 14

get\_res0, 15

get\_ring, 15

get\_uddest, 16

get\_udedge, 17

get\_udedges, 17

get\_udends, 18

get\_udorigin, 19

grid\_distance, 19

grid\_path, 20

h3\_info\_table, 21

h3\_to\_line, 22

h3\_to\_point, 23

h3\_to\_polygon, 24

h3jsr (h3jsr-package), 3

h3jsr-package, 3

h3jsr::grid\_path(), 22

is\_pentagon, 24

is\_rc3, 25

is\_valid, 26

is\_valid\_edge, 26

point\_to\_h3, 27

polyfill, 4, 28

res\_area, 29

res\_cendist, 29

res\_count, 30

res\_length, 31

set\_to\_multipolygon, 31

udedge\_to\_line, 32

uncompact, 33