

# Package ‘mlr3tuningspaces’

December 7, 2022

**Title** Search Spaces for 'mlr3'

**Version** 0.3.3

**Description** Collection of search spaces for hyperparameter optimization in the mlr3 ecosystem. It features ready-to-use search spaces for many popular machine learning algorithms. The search spaces are from scientific articles and work for a wide range of data sets.

**License** LGPL-3

**URL** <https://mlr3tuningspaces.mlr-org.com>,  
<https://github.com/mlr-org/mlr3tuningspaces>

**BugReports** <https://github.com/mlr-org/mlr3tuningspaces/issues>

**Depends** mlr3tuning (>= 0.15.0), R (>= 3.1.0)

**Imports** checkmate (>= 2.0.0), data.table (>= 1.14.0), mlr3 (>= 0.11.0), mlr3misc (>= 0.11.0), paradox (>= 0.7.1), R6 (>= 2.5.0)

**Suggests** e1071 (>= 1.7-6), glmnet (>= 4.1-2), kknn (>= 1.3.1), mlr3learners (>= 0.4.5), ranger (>= 0.12.1), rpart (>= 4.1-15), testthat (>= 3.0.0), xgboost (>= 1.4.1.1)

**Config/testthat/edition** 3

**Encoding** UTF-8

**RoxygenNote** 7.2.2

**Collate** 'mlr\_tuning\_spaces.R' 'TuningSpace.R' 'bibentries.R' 'sugar.R'  
'tuning\_spaces\_default.R' 'tuning\_spaces\_rbv2.R' 'zzz.R'

**NeedsCompilation** no

**Author** Marc Becker [cre, aut] (<<https://orcid.org/0000-0002-8115-0400>>),  
Michel Lang [ctb] (<<https://orcid.org/0000-0001-9754-0393>>)

**Maintainer** Marc Becker <marcbecker@posteo.de>

**Repository** CRAN

**Date/Publication** 2022-12-07 14:10:02 UTC

## R topics documented:

mlr3tuningspaces-package	2
lts	3
mlr_tuning_spaces	4
mlr_tuning_spaces_default	5
mlr_tuning_spaces_rbv2	6
TuningSpace	8

<b>Index</b>	<b>11</b>
--------------	-----------

---

mlr3tuningspaces-package

*mlr3tuningspaces: Search Spaces for 'mlr3'*

---

### Description

Collection of search spaces for hyperparameter optimization in the mlr3 ecosystem. It features ready-to-use search spaces for many popular machine learning algorithms. The search spaces are from scientific articles and work for a wide range of data sets.

### Author(s)

**Maintainer:** Marc Becker <marcbecker@posteo.de> ([ORCID](#))

Other contributors:

- Michel Lang <michellang@gmail.com> ([ORCID](#)) [contributor]

### See Also

Useful links:

- <https://mlr3tuningspaces.mlr-org.com>
- <https://github.com/mlr-org/mlr3tuningspaces>
- Report bugs at <https://github.com/mlr-org/mlr3tuningspaces/issues>

lts

*Syntactic Sugar for Tuning Space Construction***Description**

Function to retrieve [TuningSpace](#) objects from [mlr\\_tuning\\_spaces](#) and further, allows a [mlr3::Learner](#) to be directly configured with a search space. This function belongs to [mlr3::mlr\\_sugar](#) family.

**Usage**

```
lts(x, ...)

## S3 method for class 'missing'
lts(x, ...)

## S3 method for class 'character'
lts(x, ...)

## S3 method for class 'Learner'
lts(x, ...)

ltss(x)
```

**Arguments**

x	( <a href="#">character()</a>   <a href="#">mlr3::Learner</a> ) If <a href="#">character</a> , key passed the dictionary to retrieve the tuning space. If <a href="#">mlr3::Learner</a> , default tuning space is added to the learner.
...	(named list of <a href="#">paradox::TuneToken</a>   NULL) Pass <a href="#">paradox::TuneToken</a> to add or overwrite parameters in the tuning space. Use NULL to remove parameters (see examples).

**Value**

[TuningSpace](#) if x is [character\(\)](#). [mlr3::Learner](#) if x is [mlr3::Learner](#). Or a list of objects for the [ltss\(\)](#) function.

missing, [mlr\\_tuning\\_spaces](#) dictionary

a [character](#), [TuningSpace](#)

a [mlr3::Learner](#), [mlr3::Learner](#) with [paradox::TuneToken](#)

a [list\(\)](#), list of [TuningSpace](#) or [mlr3::Learner](#)

**Examples**

```
# load tuning space
lts("classif.rpart.default")
```

```

# load tuning space and add parameter
lts("classif.rpart.default", maxdepth = to_tune(1, 15))

# load tuning space and remove parameter
lts("classif.rpart.default", minsplit = NULL)

# load tuning space and overwrite parameter
lts("classif.rpart.default", minsplit = to_tune(32, 128))

# load learner and apply tuning space in one go
lts(lrn("classif.rpart"))

# load learner, overwrite parameter and apply tuning space
lts(lrn("classif.rpart"), minsplit = to_tune(32, 128))

# load multiple tuning spaces
ltss(c("classif.rpart.default", "classif.ranger.default"))

```

---

mlr\_tuning\_spaces      *Dictionary of Tuning Spaces*

---

## Description

A simple `mlr3misc::Dictionary` storing objects of class `TuningSpace`. Each tuning space has an associated help page, see `mlr_tuning_spaces_[id]`.

## Format

`R6::R6Class` object inheriting from `mlr3misc::Dictionary`.

## Methods

See `mlr3misc::Dictionary`.

## S3 methods

- `as.data.table(dict, ..., objects = FALSE)`  
`mlr3misc::Dictionary -> data.table::data.table()`  
Returns a `data.table::data.table()` with fields "key", "label", "learner", and "n\_values" as columns. If `objects` is set to `TRUE`, the constructed objects are returned in the list column named `object`.

## Examples

```

as.data.table(mlr_tuning_spaces)
mlr_tuning_spaces$get("classif.ranger.default")
lts("classif.ranger.default")

```

---

`mlr_tuning_spaces_default`*Default Tuning Spaces*

---

**Description**

Tuning spaces from the Bischl (2021) article.

**glmnet tuning space**

- `s` [ $1e - 04$ , 10000]
- `alpha` [0, 1]

**kknn tuning space**

- `k` [1, 50]
- `distance` [1, 5]
- `kernel` ["rectangular", "optimal", "epanechnikov", "biweight", "triweight", "cos", "inv", "gaussian", "rank"]

**ranger tuning space**

- `mtry.ratio` [0, 1]
- `replace` [TRUE, FALSE]
- `sample.fraction` [0.1, 1]
- `num.trees` [1, 2000]

**rpart tuning space**

- `minsplit` [2, 128]
- `minbucket` [1, 64]
- `cp` [ $1e - 04$ , 0.1]

**svm tuning space**

- `cost` [ $1e - 04$ , 10000]
- `kernel` ["polynomial", "radial", "sigmoid", "linear"]
- `degree` [2, 5]
- `gamma` [ $1e - 04$ , 10000]

**xgboost tuning space**

- eta [ $1e - 04$ , 1]
- nrounds [1, 5000]
- max\_depth [1, 20]
- colsample\_bytree [0.1, 1]
- colsample\_bylevel [0.1, 1]
- lambda [0.001, 1000]
- alpha [0.001, 1000]
- subsample [0.1, 1]

**Source**

Bischl B, Binder M, Lang M, Pielok T, Richter J, Coors S, Thomas J, Ullmann T, Becker M, Boulesteix A, Deng D, Lindauer M (2021). “Hyperparameter Optimization: Foundations, Algorithms, Best Practices and Open Challenges.” 2107.05847, <https://arxiv.org/abs/2107.05847>.

---

mlr\_tuning\_spaces\_rbv2

*RandomBot Tuning Spaces*

---

**Description**

Tuning spaces from the Kuehn (2018) article.

**glmnet tuning space**

- alpha [0, 1]
- s [ $1e - 04$ , 1000]

**kknn tuning space**

- k [1, 30]

**ranger tuning space**

- num.trees [1, 2000]
- replace [TRUE,FALSE]
- sample.fraction [0.1, 1]
- mtry.ratio [0, 1]
- respect.unordered.factors [“ignore”, “order”, “partition”]
- min.node.size [1, 100]
- splitrule [“gini”, “extratrees”]
- num.random.splits [1, 100]

mtry.power is replaced by mtry.ratio.

**rpart tuning space**

- cp [ $1e - 04$ , 1]
- maxdepth [1, 30]
- minbucket [1, 100]
- minsplit [1, 100]

**svm tuning space**

- kernel [“linear”, “polynomial”, “radial”]
- cost [ $1e - 04$ , 1000]
- gamma [ $1e - 04$ , 1000]
- tolerance [ $1e - 04$ , 2]
- degree [2, 5]

**xgboost tuning space**

- booster [“gblinear”, “gbtree”, “dart”]
- nrounds [2, 8]
- eta [ $1e - 04$ , 1]
- gamma [ $1e - 05$ , 7]
- lambda [ $1e - 04$ , 1000]
- alpha [ $1e - 04$ , 1000]
- subsample [0.1, 1]
- max\_depth [1, 15]
- min\_child\_weight [1, 100]
- colsample\_bytree [0.01, 1]
- colsample\_bylevel [0.01, 1]
- rate\_drop [0, 1]
- skip\_drop [0, 1]

**Source**

Kuehn D, Probst P, Thomas J, Bischl B (2018). “Automatic Exploration of Machine Learning Experiments on OpenML.” 1806.10961, <https://arxiv.org/abs/1806.10961>.

---

TuningSpace

*Tuning Spaces*


---

## Description

This class defines a tuning space for hyperparameter tuning.

For tuning, it is important to create a search space that defines the range over which hyperparameters should be tuned. TuningSpace object consists of search spaces from peer-reviewed articles which work well for a wide range of data sets.

The `$values` field stores a list of [paradox::TuneToken](#) which define the search space. These tokens can be assigned to the `$values` slot of a learner's [paradox::ParamSet](#). When the learner is tuned, the tokens are used to create the search space.

## S3 Methods

- `as.data.table.TuningSpace(x)`  
Returns a tabular view of the tuning space.  
[TuningSpace](#) -> `data.table::data.table()`

– `x` ([TuningSpace](#))

## Public fields

`id` (`character(1)`)  
Identifier of the object.

`values` (`list()`)  
List of [paradox::TuneToken](#) that describe the tuning space and fixed parameter values.

`tags` (`character()`)  
Arbitrary tags to group and filter tuning space e.g. "classification" or "regression".

`learner` (`character(1)`)  
[mlr3::Learner](#) of the tuning space.

`package` (`character(1)`)  
Packages which provide the [Learner](#), e.g. [mlr3learners](#) for the learner [mlr3learners::LearnerClassifRanger](#) which interfaces the [ranger](#) package.

`label` (`character(1)`)  
Label for this object. Can be used in tables, plot and text output instead of the ID.

`man` (`character(1)`)  
String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.



**Methods****Public methods:**

- [TuningSpace\\$new\(\)](#)
- [TuningSpace\\$get\\_learner\(\)](#)
- [TuningSpace\\$format\(\)](#)
- [TuningSpace\\$help\(\)](#)
- [TuningSpace\\$print\(\)](#)
- [TuningSpace\\$clone\(\)](#)

**Method** `new()`: Creates a new instance of this [R6](#) class.

*Usage:*

```
TuningSpace$new(
  id,
  values,
  tags,
  learner,
  package = character(),
  label = NA_character_,
  man = NA_character_
)
```

*Arguments:*

`id` (`character(1)`)

Identifier for the new instance.

`values` (`list()`)

List of [paradox::TuneToken](#) that describe the tuning space and fixed parameter values.

`tags` (`character()`)

Tags to group and filter tuning spaces e.g. "classification" or "regression".

`learner` (`character(1)`)

[mlr3::Learner](#) of the tuning space.

`package` (`character()`)

Packages which provide the [Learner](#), e.g. [mlr3learners](#) for the learner [mlr3learners::LearnerClassifRanger](#) which interfaces the [ranger](#) package.

`label` (`character(1)`)

Label for the new instance. Can be used in tables, plot and text output instead of the ID.

`man` (`character(1)`)

String in the format `[pkg]::[topic]` pointing to a manual page for for the new instance. The referenced help package can be opened via method `$help()`.

**Method** `get_learner()`: Returns a learner with [TuneToken](#) set in parameter set.

*Usage:*

```
TuningSpace$get_learner(...)
```

*Arguments:*

`...` (named `'list()'`)

Passed to `mlr3::lrn()`. Named arguments passed to the constructor, to be set as parameters in the [paradox::ParamSet](#), or to be set as public field. See `mlr3misc::dictionary_sugar_get()` for more details.

*Returns:* [mlr3::Learner](#)

**Method** `format()`: Helper for print outputs.

*Usage:*

```
TuningSpace$format()
```

**Method** `help()`: Opens the corresponding help page referenced by field `$man`.

*Usage:*

```
TuningSpace$help()
```

**Method** `print()`: Printer.

*Usage:*

```
TuningSpace$print(...)
```

*Arguments:*

... (ignored).

**Method** `clone()`: The objects of this class are cloneable with this method.

*Usage:*

```
TuningSpace$clone(deep = FALSE)
```

*Arguments:*

`deep` Whether to make a deep clone.

## Examples

```
library(mlr3tuning)

# get default tuning space of rpart learner
tuning_space = lts("classif.rpart.default")

# get learner and set tuning space
learner = lrn("classif.rpart")
learner$param_set$values = tuning_space$values

# tune learner
instance = tune(
  method = "random_search",
  task = tsk("pima"),
  learner = learner,
  resampling = rsmp("holdout"),
  measure = msr("classif.ce"),
  term_evals = 10)

instance$result
```

# Index

- \* **Dictionary**
  - mlr\_tuning\_spaces, 4
- \* **TuningSpace**
  - mlr\_tuning\_spaces, 4
- \* **datasets**
  - mlr\_tuning\_spaces, 4

data.table::data.table(), 4, 8

Learner, 8, 9

lts, 3

ltss (lts), 3

mlr3::Learner, 3, 8–10

mlr3::mlr\_sugar, 3

mlr3learners::LearnerClassifRanger, 8, 9

mlr3misc::Dictionary, 4

mlr3tuningspaces

- (mlr3tuningspaces-package), 2

mlr3tuningspaces-package, 2

mlr\_tuning\_spaces, 3, 4

mlr\_tuning\_spaces\_classif.glmnet.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_classif.glmnet.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_classif.kknn.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_classif.kknn.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_classif.ranger.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_classif.ranger.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_classif.rpart.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_classif.rpart.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_classif.svm.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_classif.svm.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_classif.xgboost.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_classif.xgboost.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_default, 5

mlr\_tuning\_spaces\_rbv2, 6

mlr\_tuning\_spaces\_regr.glmnet.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_regr.glmnet.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_regr.kknn.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_regr.kknn.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_regr.ranger.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_regr.ranger.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_regr.rpart.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_regr.rpart.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_regr.svm.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_regr.svm.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

mlr\_tuning\_spaces\_regr.xgboost.default

- (mlr\_tuning\_spaces\_default), 5

mlr\_tuning\_spaces\_regr.xgboost.rbv2

- (mlr\_tuning\_spaces\_rbv2), 6

paradox::ParamSet, 8, 9

paradox::TuneToken, 3, 8, 9

R6, 9

R6::R6Class, 4

TuneToken, 9

TuningSpace, 3, 4, 8, 8